



SAFETY DATA SHEET

1. Identification

Product identifier DUROCK® Cement Board (with or without EdgeGuard™)

Other means of identification

SDS number 14000010001

Synonyms Cement Underlayment Board, Cement Panels

Recommended use Interior or exterior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer United States Gypsum Company

Address 550 West Adams Street
Chicago, Illinois 60661-3637

Telephone 1-800-874-4968

Website www.usg.com

Emergency phone number 1-800-507-8899

Supplier CGC Inc.

Address 350 Burnhamthorpe Road West, 5th Floor
Mississauga, Ontario L5B 3J1
A Subsidiary of USG Corporation

Telephone 1-800-387-2690

Website www.cgcinc.com

Emergency phone number 1-800-507-8899

2. Hazard identification

Physical hazards Not classified.

Health hazards

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Sensitization, skin	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity following single exposure	Category 3 respiratory tract irritation

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer.

Precautionary statements

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response	IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Portland Cement	65997-15-1	< 50
Fly ash	68131-74-8	< 20
Calcium sulfate dihydrate (alternative CAS 10101-41-4)	13397-24-5	< 10
Perlite	93763-70-3	< 10
Continuous filament glass fiber	65997-17-3	< 5

Impurities	CAS number	%
Crystalline silica (Quartz)	14808-60-7	< 0.7

Composition comments	Occupational Exposure Limits for impurities are listed in Section 8. All concentrations are in percent by weight. Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 0.7%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.
-----------------------------	---

4. First-aid measures

Inhalation	Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.
Skin contact	Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.
Eye contact	Dust in eyes: Flush with cold tap water for at least 15 minutes. If irritation persists, seek medical attention immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause chemical eye burns. Permanent eye damage including blindness could result. Dust may cause skin, eye, throat and respiratory system irritation and cause coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not applicable.
Specific hazards arising from the chemical	Not a fire hazard.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials.
Specific methods	Cool material exposed to heat with water spray and remove it if no risk is involved.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	No specific clean-up procedure noted. For waste disposal, see Section 13 of the SDS.
Environmental precautions	Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling	Use work methods which minimise dust production. Avoid inhalation of dust and contact with skin and eyes. Wash hands after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store all DUROCK® Panels flat. Store in an enclosed materials shelter providing protection from damage and exposure to the elements.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Continuous filament glass fiber (CAS 65997-17-3)	TWA	1 fibers/cm ³	Respirable fibers (length > 5 µm & aspect ratio ≥ 3:1)
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m ³	Respirable fraction.
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m ³	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Continuous filament glass fiber (CAS 65997-17-3)	TWA	0.2 fibers/cm ³	Fiber.
		5 mg/m ³	Fiber, total
		5 mg/m ³	Total particulate.
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable particles.
Perlite (CAS 93763-70-3)	TWA	3 mg/m ³	Respirable particles.
		10 mg/m ³	Total particulate.
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m ³	
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m ³	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Continuous filament glass fiber (CAS 65997-17-3)	TWA	0.2 fibers/cm ³	Fiber.
		5 mg/m ³	Inhalable fibers.
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
Perlite (CAS 93763-70-3)	TWA	3 mg/m ³	Respirable fraction.
		10 mg/m ³	Total dust.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Continuous filament glass fiber (CAS 65997-17-3)	TWA	0.5 fibers/ml	Respirable fibers.
		5 mg/m3	Inhalable fraction.
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Perlite (CAS 93763-70-3)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Triethanolamine (CAS 102-71-6)	TWA	3.1 mg/m3	
		0.5 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Continuous filament glass fiber (CAS 65997-17-3)	TWA	1 fibers/cm3n	Fiber.
		10 mg/m3	Total dust.
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Perlite (CAS 93763-70-3)	TWA	10 mg/m3	Total dust.
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimise the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles.

Skin protection

Hand protection

It is a good industrial hygiene practice to minimise skin contact. For prolonged or repeated skin contact use suitable protective gloves.

Other

Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure air supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.

Thermal hazards None.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Board.

Colour Grey.

Odour Low to no odour.

Odour threshold Not applicable.

pH 12

Melting point/freezing point Not applicable.

Initial boiling point and boiling range Not applicable.

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not applicable.

Flammability limit - upper (%) Not applicable.

Explosive limit - lower (%) Not applicable.

Explosive limit - upper (%) Not applicable.

Vapour pressure Not applicable.

Vapour density Not applicable.

Relative density 0.8 - 1.2 (H₂O=1)

Solubility(ies)

Solubility (water) Insoluble.

Partition coefficient (n-octanol/water) Not applicable.

Auto-ignition temperature Not applicable.

Decomposition temperature Not applicable.

Viscosity Not applicable.

Other information

Bulk density 60 - 65 lb/ft³

Explosive properties Not explosive.

Oxidising properties Not oxidising.

VOC 0 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	Calcium oxides. Sulphur oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne respirable crystalline silica can cause silicosis and/or lung cancer.
Skin contact	Dust can be irritating to skin.
Eye contact	Causes serious eye damage.
Ingestion	Ingestion may cause irritation and stomach discomfort.

Symptoms related to the physical, chemical and toxicological characteristics May cause chemical eye burns. Permanent eye damage or blindness could result. Dust may irritate eyes, skin, throat and upper respiratory system and cause coughing.

Information on toxicological effects

Acute toxicity	Not expected to be a hazard under normal conditions of intended use.
Skin corrosion/irritation	Dust can cause skin irritation.
Serious eye damage/eye irritation	Causes serious eye damage.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant	
Continuous filament glass fiber (CAS 65997-17-3)	Irritant
Triethanolamine (CAS 102-71-6)	Irritant
Canada - Quebec OELs: Sensitizer	
Triethanolamine (CAS 102-71-6)	Sensitiser.

Respiratory sensitisation Not a sensitizer.

Skin sensitisation Trace amounts of Cr(VI) compounds from Portland Cement may cause allergic skin reaction even after one exposure.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Repeated and prolonged exposure to high levels of respirable crystalline silica may cause cancer.

ACGIH Carcinogens

Continuous filament glass fiber (CAS 65997-17-3)	A2 Suspected human carcinogen.
Crystalline silica (Quartz) (CAS 14808-60-7)	A2 Suspected human carcinogen.
Portland Cement (CAS 65997-15-1)	A4 Not classifiable as a human carcinogen.

Canada - Alberta OELs: Carcinogen category

Continuous filament glass fiber (CAS 65997-17-3)	Suspected human carcinogen.
Crystalline silica (Quartz) (CAS 14808-60-7)	Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Continuous filament glass fiber (CAS 65997-17-3)	Suspected human carcinogen.
Crystalline silica (Quartz) (CAS 14808-60-7)	Suspected human carcinogen.
Portland Cement (CAS 65997-15-1)	Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

Continuous filament glass fiber (CAS 65997-17-3)	Detected carcinogenic effect in animals.
Crystalline silica (Quartz) (CAS 14808-60-7)	Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Continuous filament glass fiber (CAS 65997-17-3)	3 Not classifiable as to carcinogenicity to humans.
Crystalline silica (Quartz) (CAS 14808-60-7)	1 Carcinogenic to humans.
Triethanolamine (CAS 102-71-6)	3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Continuous filament glass fiber (CAS 65997-17-3)	Reasonably Anticipated to be a Human Carcinogen.
Crystalline silica (Quartz) (CAS 14808-60-7)	Known To Be Human Carcinogen.

Reproductive toxicity Not expected to be a reproductive hazard.

Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Not classified. For detailed information, see section 16.
Aspiration hazard	Due to the physical form of the product it is not an aspiration hazard.
Chronic effects	Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to the lung disease known as silicosis. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

12. Ecological information

Ecotoxicity	The product is not expected to be hazardous to the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	Bioaccumulation is not expected.
Mobility in soil	No data available.
Other adverse effects	None expected.

13. Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Not regulated.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

14. Transport information

TDG	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

Canadian regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.
Controlled Drugs and Substances Act	Not regulated.
Export Control List (CEPA 1999, Schedule 3)	Not listed.
Greenhouse Gases	Not listed.
Precursor Control Regulations	Not regulated.
International regulations	
Stockholm Convention	Not applicable.
Rotterdam Convention	Not applicable.
Kyoto Protocol	Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Continuous filament glass fiber (CAS 65997-17-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information**Issue date** 03-May-2018**Revision date** -**Version No.** 01

Further information Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material.

The ACGIH has established a TLV (Threshold Limit Value or recommended exposure limit) for continuous filament glass fiber of 1 fiber per cubic centimeter of air for respirable fibers and 5 mg per cubic meter of air for inhalable glass fiber dust. These levels were established to prevent mechanical irritation of the upper airways. IARC, NTP (US National Toxicology Program) and OSHA (US Occupational Safety and Health Administration) do not list continuous filament glass fibers as a carcinogen.

As manufactured, continuous filament glass fibers in this product are not respirable. Continuous filament glass products that are chopped, crushed or severely mechanically processed during manufacturing or use may contain a very small amount of respirable particulate, some of which may be glass shards.

NFPA Ratings:
 Health: 2
 Flammability: 0
 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

List of abbreviations NFPA: National Fire Protection Association.**Disclaimer** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.