Sport Wheelchairs



With Camber Angles 2 Degrees or Above

Client Cont	act Informa	tion							
Client Name	ne:			Dat	Date:				
Address 1:									
Address 2:									
City:					٥.	7	in:		
-					e:		ip:		
Phone #:									
Email:									
ATP/Therap	DIST/RWC S	pecialist							
Name:									
Phone #:									
Email:									
Chair Model		Description							
RWC-WC003 RWC-WC004	H	Fastbreak Ba		a combor obovo 2 de	2000)				
RWC-WC004		Drop Shot Ter		camber above 2 de	egrees)				
RWC-WC005	H	_	ugby League (Chair					
RWC-WC011		Touchdown F							
Seat Width									
	12"	 	13"		14"		15"		
	16"		17"		18"		19"		
	20"								
	Other:								
Seat Depth									
	12"	ΙП	13"		14"		15"		
	16"		17"		18"		19"		
	20"								
	Other:								
Front Seat Heig									
	17"		17.5"		18"		18.5"		
	19"		19.5"		20"		20.5"		
	Other:								
Wheel Size			Boor Hoigh	nt Range (.5" Increm	ionto)	Boar Soot H	oight (E" Ingram	vonts)	
Wileel Size	24" Wheel (54	0)	14" to 18.5		ange (.5 increments)		Rear Seat Height (.5" Increments)		
H H	25" Wheel (559		15" to 19.5			Inch	Inches:		
	26" Wheel (59		16" to 21"						
	700c Wheel (6	22)	16" to 21"						
Ergo	No		Voc	Note: De E	a with a December	of 2 Finess and			
	-	oo).	Yes Note: Do Ergo with a Dump of 3.5 inces or less						
	Ergo (Inches):								

Frame Oprtion (Default is No)										
Tow Handle On Camber Tube										
Front	Angle									
TTOTAL	7 trigic	90 Degree Stand	dard		Other					
	$\overline{\Box}$	Front Angle								
		<u> </u>								
Cente	er of Gravity	У								
		2"		2.5"		3"		3.5"		
		4"		4.5"		5"		5.5"		
		6"		6.5"		7"		7.5"		
		Other:								
Anti-	Tip Bars	0: 1 (1) 15								
	<u> </u>	Single (Not Free								
	+	Removable Anti- Double (Not Fre								
		Double (Not i le	c on every chair	,						
Picke	r Bar									
		Flat 3 Point		3/4"		1.25"		1.25'	' - Extra Thick	
		5 Point		3/4"		1.25"	•	•		
		Round		1.25"		1.25" - Extra	Thick			
Back	Post Heigh		ard backs do no	ot need as high of	a back post)		Back Post	Height		
	+	Low		Up to 9" 9" to 12"		Inches				
		High		12" and Up		"	Inches:			
		<u> </u>		aa op						
Back	Angle									
		90 Degree Stand		Other						
		Back Angle	:							
Caml	per Angle									
	<u> </u>	16 Degree		18 Degree		20 Degree				
		Other Angle	9:							
0	Oi	Oalan								
Caste	er Size and	72mm Speed W	haals							
		Other:	TICCIS							
		Other.								
Sling	To Footpla	te (Keep in mind	Seat Cushion)	Front Taper						
J9	io i ootpia	to (1.100p III. 11III.10	out outilion,		None or					
Inches:			Inches							
Caste	er Width			Camber Tube t	o Front Caster		Camber T	ube to Front	Down Tube	
Inches:			Inches	Inches:				Inches:		
Inches:			liiciles	Inches:						
				1						
Prima	ary Powder	Number From Pr	rismatics	Primary Powde	er Coat Name F	orm Prismatics				
Numl				Name:						

Secondary Powder Number From Prismatics		Secondary Powder Coat Name Form Prismatics							
Number		Name							
Number:		Name:							
Backrest									
Dackrest	Adjustable Softback								
- i	ADI Carbon Fiber - Active	Low (10")							
	ADi Carbon Fiber - Deep	Low (10")							
	Other:								
	- Curior:								
Seat Cushion									
	Standard Seat								
	Other List in box below:								
	-								
Make and Mod	lel:								
0 10 11									
Seat Options									
	Carbon Fiber Seat Pan								
First Set of Wh	naels								
Thist Set of Wi	Standard Spinergy XSLX								
i i	Standard Spinergy XSLX "R10"								
	Other:								
	Other.								
Axle Size									
	1/2"	5/8"							
Second Set of	Wheels								
	Other:								
	•								
Handrims									
	Standard Hard Anodized Handrii	ms							
	Airgrip Handrims (\$\$)								
	Q-Grip Handrims (\$\$)								
	Other (\$\$):								
Handrim Place									
	First Hole (Farthest out)	Second Hole (Mid way) Third Hole (Close In)							
Tiros	Description.								
Tires	Street	Description Character Division							
	Sport	eg Marathon Plus							
H	Sport eg Kontenders Solid eg Primo Solids								
	Other or Specify:								
	other or openity.								
Wheel Locks									
	No								
	Other:								
	- C. 101.								

Side Guards		Side guard height									
	Carbon Fiber										
	Aluminum Standard		Bolted		Welded						
	Sideguard Height		1/4" Bellow Tire		At Tire		1/4" Above Tire				
	Other:										
	-										
Accessories											
	Leather Impact Guards (\$\$)										
	Seat Belt (Double Pull) (\$\$)		1"		1.5"						
	Calf Strap (\$\$)		3"		6"						
	M2 Straps		Hip		Knee (\$\$)		Foot				
	Removable Anti-Tip 5th Wheel (\$	Removable Anti-Tip 5th Wheel (\$\$)									
	Other:										
Graphics											
	Vinyl Graphics on Side guards (\$										
	Laser Graphic on Footplate (Dep		er Coating Choice)								
	Sewn on Flag or Military Embroidery										
	Specify Sew On:										
Shipping	_										
	Pickup in Houston										
	Shipping in USA (\$\$)										
	Shipping outside the USA (\$\$)	Shipping outside the USA (\$\$)									
	Other:										
Notes:											