

Floor Lacquer (two pack)

For internal wooden floors. New technology two-pack solvent-based lacquer providing a beautiful, tactile, and durable finish.

Available in a range of finishes from matt to high gloss.
Perfect for high traffic areas.



- ✓ Moisture and chemical resistant
- ✓ Isocyanate free
- ✓ Hydrocarbon free

PHYSICAL PROPERTIES

Flash point	21°C
Coverage	12m ² /litre
Appearance	Clear / milky
Solid content	40%
Viscosity @ 23°C	24+2 seconds
Touch dry	20 to 30 minutes

FINISH	GLOSS @ 60'
Matt	10%
Eggshell	20%
Silk	40%
Gloss	90%

SURFACE PREPARATION

Remove all loose contamination from substrate such as dust and dirt. All surfaces should be grease free and sanded ready to be coated. Wipe the surface with White Spirit.

Ideal for use over Trade Coatings Wood Stain, or coat-on-coat application with a light sand in between each coat.

If using on MDF we recommend the use of Trade Coatings MDF Sealer first as a base coat.

APPLICATION

Supplied with correct ratio amount of catalyst. Pour all into main container and mix thoroughly. If using part quantities, ensure catalyst is added to the same ratio.

Suitable for brush, roller, or spray application. Allow at least 30 minutes drying time before sanding and overcoating (longer in temperatures below 18°C).

For airless spray use a 1.7mm or 1.8mm nozzle. If necessary, thin with Trade Coatings Thinner.

CURING AND AFTERCARE

Achieves full durable hardness over a period of a few weeks. For cleaning the surface during this period use a damp soft cloth or mop.

HANDLING AND STORAGE

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Shelf life is 24 months under above mentioned storage conditions.

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SAFETY

Pre-catalysed lacquers are skin and eye irritants and sensitisers. It is extremely important to wear protective gloves and eye protection when handling. Spills or splashes must be removed immediately – if allowed to dry, material can only be removed mechanically or with heat and/or harsh chemicals.

Environmentally hazardous - do not allow wet product to enter water courses, drains, sewers or the general environment.

For professional use only.

FIRST AID

EYE CONTACT

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

INHALATION

Seek fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

SKIN CONTACT

Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

INGESTION

If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention, show the container label. Protection of first aiders: No action shall be taken involving any personal risk or without suitable training.

FIREFIGHTING MEASURES

EXTINGUISHING MEDIA

Carbon oxides.

FIRE HAZARDS

Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

PROTECTIVE EQUIPMENT

Self-contained breathing apparatus. Wear protective clothing.

SYMBOLS

F - Highly flammable; Xi - Irritant

RISK PHRASES

R11 - Highly flammable.

R36 - Irritating to eyes.

R67 - Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S1/2 - Keep locked up and out of the reach of children.

S13 - Keep away from food, drink, and animal feeding stuffs.

S16 - Keep away from sources of ignition - no smoking.

S46 - If swallowed, seek medical advice immediately and show this container or label.



TradeCoatings®

The advice and information given in this data sheet is given freely and in good faith and is based upon data that we believe is reliable. The data herein is based on extensive laboratory testing and experience, but we cannot test for every eventuality. It remains the customer's responsibility to ensure the product is fit for intended purpose. Trade Coatings cannot guarantee anything but the quality of the product and cannot be held responsible for results obtained.