

Universal Surface Paint

Tough, versatile, and easy to use external paint suitable for all surfaces. Fast drying, washable and provides long lasting impact resistance and corrosion protection.

100% VOC-FREE AND ODOUR-FREE


No solvents or spirits are release into atmosphere when using this product. Perfect for use where a non-hazardous product would be preferred, such as education healthcare, occupied commercial and public buildings. Also safe for internal use.


- ✓ All-in-one product (primer, undercoat, and topcoat)
- ✓ Fast drying
- ✓ Decorates, protects, and rejuvenates


PERFECT FOR:


- | | | |
|-------------|-----------------------|---------------|
| ✓ Wood | ✓ Concrete | ✓ Brick |
| ✓ Render | ✓ Asbestos | ✓ Asphalt |
| ✓ Copper | ✓ Slate | ✓ Galvanising |
| ✓ Plastics | ✓ Iron | ✓ Surfaces |
| ✓ Bitumen | ✓ Lead | ✓ Steel |
| ✓ Aluminium | ✓ Rubberised surfaces | |




 Water-based coating with high build acrylic polymer resins


 Microporous and breathable

 Resists cracking and flaking

 Heat resistant to 80°C

 100% VOC-free

 Alkali resistant

 Quick drying – recoatable in 4hrs

 Non-flammable

PHYSICAL PROPERTIES

Flash point	n/a
Coverage	12-14m ² /litre
Appearance	As per colour choice
Solid content	38%
Viscosity @ 23°C	28 seconds
Drying time	Touch dry 15 to 20 minutes

SURFACE PREPARATION

The substrate must be sound, dry, and free from oil and grease. Cleaning should be carried out with liquid detergent solution, rinsed with clean water, and allowed to dry.

Surfaces which are contaminated with lichen or moss should be brushed clean, treated with Anti-Fungal Wash, and allowed to dry.

Any repairs should be carried out before application. Plastic, rubberised and metal surfaces should be rubbed down with abrasive paper prior to application.

APPLICATION

Suitable for brush, roller, or spray application (dilute with 10% water if spraying). No primer or undercoat is necessary unless used on ferrous metal or where staining could occur. For very porous substrates thin the first coat with 30% water.

For best results apply to a touch dry surface, and at temperatures between 10°C to 32°C. Do not apply at temperatures below 8°C. Ensure good ventilation during and after application. Wear gloves, goggles, and suitable PPE.

Optimum hardness is reached after 2 weeks. Ensure good ventilation during application and drying.

STORAGE GUIDELINES

Store indoors, away from direct sunlight in original container, in a dry place at temperature between 5 and 40°C.

Keep out of reach of children.

Shelf life is 12 months under above mentioned storage conditions.

FIRST AID

EYE CONTACT

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

INHALATION

Seek fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

SKIN CONTACT

Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

INGESTION

If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention, show the container label. Protection of first aiders: No action shall be taken involving any personal risk or without suitable training.



TradeCoatings[®]

The advice and information given in this data sheet is given freely and in good faith and is based upon data that we believe is reliable. The data herein is based on extensive laboratory testing and experience, but we cannot test for every eventuality. It remains the customers responsibility to ensure the product is fit for intended purpose. Trade Coatings cannot guarantee anything but the quality of the product and cannot be held responsible for results obtained.