

TE-YL5S Series

Interactive Flat Panel Display

Android 11 Series 3 – Performance Leader

65" | 75" | 86"



Premium model, super slim form factor and wide viewing angles. Features 4K resolution, enhanced CPU/GPU, and Type-C port. Secured Android login allows for up to 9 account profiles.

- Smooth annotation with multi-finger gesture functionality
- Wireless screen sharing up to 9 devices (any operating system)
- Meeting notes shared by auto-generated QR code for mobile devices.
- OTA helps future-proof panel by providing over-the-air firmware and software feature updates.



All-in-One

Integrates all these functions:

- ✓ Large format interactive display
- ✓ Command control via touch
- ✓ Android tablet functions
- ✓ Interactive kiosk with audio



Narrow bezel

Screen utilization rate reaches 98%. Advanced IR filter technology for a more natural writing experience



Dual System

Supports Android and Windows OS. Each system can be operated and managed separately. Elegant simplified UI for Android.



UHD 4K Resolution

Android 11 utilizes 4K quality. High-precision UHD picture for improved visual experience. Zero Gap Screen Design.

Quick and high accuracy infrared multi-touch

- ✓ Up-to-20 points of touch
- ✓ Intelligent gesture recognition supports additional functions.



Annotation

Annotate on Android or Windows applications with SBS Note. No lag and no parallax.

| Model | TE-YL5S-65 | | | TE | -YL5S- | 75 <u> </u> | | TE-YL5S-86 | |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|-----------|-------------------------------------|-----------------------------------------------------|-------------------------------------------------------------|---------------------------|-------------------------------------------------|--|
| Display Backlight | D-LED | | | | | | | | |
| Resolution | 3840*2160 | | | | | | | | |
| Brightness | 350 cd/m ² | | | | | | | | |
| Contrast | 1200:1 or higher | | | | | | | | |
| Screen Size(") | 56.2 * 31.6 | | | 64. | 96 * 36 | .54 | | 74.6 * 41.9 | |
| Aspect Ratio | | | | 16: | 9 | | | | |
| View Angle | 178° | | | | | | | | |
| Screen Mode | 16:9/4:3/dot to dot/full screen | | | | | | | | |
| Color Depth | 10bit, 1.07Billon colors | | | | | | | | |
| Panel Response Time | 8ms | | | | | | | | |
| Support Resolution | | | 4K | Ultra HD | 3840x2 | 160 | | | |
| Android Specification | Android 11.0 | | | | | | | | |
| | CPU: A73*4 + A53*4@2.28GHz, GPU: G52*8 | | | | | | | | |
| | RAM: 8G DDR4 | | | | | | | | |
| | Storage: 64G EMMC | | | | | | | | |
| | Full support for Full HD and 4K resolution (with OPS slot working with 4k 60Hz) | | | | | | | | |
| | The file manager is supported | | | | | | | | |
| | Screen sharing application is supported | | | | | | | | |
| | Local and online support music player. | | | | | | | | |
| Input Ports | 1*OPS slot (up to3840*2160/60Hz) Front: 1*HDMI (Max support 3840*2160/60Hz), 1*TOUCH USB, 3*USB 3.0, 1*Type-C | | | | | | | | |
| Output Ports | | | | • | | 、1*RJ45 | | | |
| Front Button | 8 K | EYS (POWER、S | | | | | VIE、ENTER. | (ES) | |
| Speakers | | | | 2 * 15W | | | | | |
| Voltage | Chandle Damen | AC(100 ~ 240)V-50/60HZ <1W Standby Power<1W Standby Power<1\ | | | | Chandley Dayyan (1) A/ | | | |
| Power Range | Standby Power< | | | | • | | | Standby Power<1W | |
| | Rated Power<23 | SUVV | | Rated | l Power | | h | Rated Power<415W | |
| Touch Parameter | Touch Doints | Infared Touch | | | | | | | |
| | Writing Mode | Touch Points 20 touch points Writing Mode. Finger or any opaque phiect | | | | | | | |
| | | Finger or any opaque object <2mm | | | | | | | |
| | Response Time | | | | | | | | |
| | Cusor Speed | | | | | | | | |
| | Connection Port | USB 2.0 | | | | | | | |
| | Operating System | Windows/Linux/Mac/Android | | | | | | | |
| | 0 00.00.00 | 0°C-40°C | | | | | | | |
| | Working Temperature | | | V | Vindow | | c, r in ar ora | | |
| Accessories | Temperature | Magnetic Pens* rboard Software | | Cable*1, | Touch l | 0°C-40°C JSB cable, Po | ower Cable* | | |
| Accessories Sizes(") | Temperature | rboard Software | | Cable*1, ownload* | Touch l | 0°C-40°C JSB cable, Po ote*1, Wall | ower Cable* | | |
| | Temperature Sta | rboard Software 6 | | Cable*1, ownload* 67. | Touch l *1, Rem | 0°C-40°C JSB cable, Po ote*1, Wall *3.6 | ower Cable* | racket | |
| Sizes(") | Temperature Stal 58.5*35.6*3. | rboard Software 6 kg) | | Cable*1, ownload* 67 119 / | Touch l *1, Rem .2*40.5 | 0°C-40°C JSB cable, Po ote*1, Wall *3.6 /71 kg) | ower Cable* | 76.9*45.9*3.6 | |
| Sizes(") Weights (lbs: Net/Gross) Carton Sizes (") | Temperature Stal 58.5*35.6*3.0 90 / 119 (41/54 | rboard Software 6 kg) 4 | online do | Cable*1, ownload* 67 119 / | Touch l *1, Rem .2*40.5 156 (54 .7*47.4 | 0°C-40°C JSB cable, Po ote*1, Wall *3.6 /71 kg) | ower Cable* mounting b | racket 76.9*45.9*3.6 154 / 194 (70/88 kg) | |

Mobile Stand, WebCam, Sound Bar, Doc Scanner, Smart Pen and more

Compatible with:

Optional Accessories







Windows ® is a trademark of Microsoft, Inc. Apple [®] is a registered trademark of Apple, Inc. Chrome OS $^{\mathsf{m}}$ is a registered trademarks of Google LLC Android [®] is a registered trademarks of Google LLC

CEF©RoHS