



New! 4 Tier Dome Top offers wide light spread for wider walkways and parking lots where maximum light is required. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 Watt max. incandescent, 13 Watt fluorescent.

Color: Verde green

Weight: 2.2 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Lamp Info		Ballast Info	
Type	A-19	Type	N/A
Watts	100W	120V	N/A
Shape/Size	N/A	208V	N/A
Base	N/A	240V	N/A
ANSI	N/A	277V	N/A
Hours	750	Input Watts	N/A
Lamp Lumens	1,650		
Efficacy	N/A		

## Technical Specifications

### Compliance

#### UL Listed:

Suitable for wet locations. Suitable for mounting within 4 feet of the ground.

### Electrical

#### Socket:

Medium base porcelain with all copper electrical parts and 20" leads, including a ground lead

#### Voltage:

120 volts AC

### Construction

#### Globes:

Threaded, gasketed globe protects against weather, garden sprinklers and insects. Clear glass GL 100 globes standard for 4 Tier. Clear glass GL60 globes standard for 3 Tier. GL100 white globes also available for attractive appearance and glare reduction.

#### Housing:

Die-cast aluminum housing with powder coat finish

#### Mounting Stem:

Optional 12" mounting stem with 1/2" threads on both ends available [here](#).

### Dome Top:

Wide light spread for wider walkways & parking lots where maximum light is required. Full-cutoff for narrow walkways & glare free lighting in garden areas.

### Optical

#### Lamp:

Incandescent lamp not supplied. Medium base A-19 lamps, 120V. 100 watt max.

### Other

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

**Dimensions****Features**

New Dome Top allows a wide light spread for wider walkways and parking lots

Rugged die cast aluminum housing with durable powder coating

Socket with all copper electrical parts and 20" leads

Quick and secure installation with one corrosion-proof screw

Threaded, gasketed globes for durable weatherproofing and easy relamping

12" color matched mounting stem with 1/2" threads available

Includes easy mounting 1/2" threaded nipple