

Technical Specifications

HOUSING: Slip fits over 2 7/8" and 3" OD tenons on most decorative poles. Cast aluminum housing uses A356 aluminum comprises 92.05% Aluminum, 7% Silicon, 0.35% Magnesium, 0.20% Iron, 0.20% Copper, 0.10% Manganese, and 0.10% Zinc. It is lightweight and highly corrosion-resistant, like stainless steel. Heat treated to improve strength—low impurities cause high strength and ductility.

FINISH: Cast aluminum fitter housing with textured or 60% gloss polyester powder coat finishes for maximum durability. The base aluminum material is prepared using an environmentally friendly non-chrome 2-step surface cleaning and passivation process. The process results in a more durable conversion layer than traditional chromate conversion coatings and allows maximum powder coating adhesion to the aluminum fitter.

POWERED BY THE LUMECON L-RETRO-T LIGHT ENGINE

INPUT VOLTAGE: 120-277V or 347-480V

EFFECTIVE PROJECTED AREA (EPA): 2.60 ft²

CUSTOM OPTICS: Lumecon meticulously engineered premium acrylic optical lenses to maximize the distribution and uniformity of light while minimizing cost. Our arrays distribute light at least 21% further and with 29% more uniformity than leading competitors. Lumecon custom lenses create a uniform, well-lit environment that mitigates illuminance "hot spots" and uses less wattage than typical LED area lights.



LUMECON ETD[™] SYSTEM: The enhanced thermal dissipation system engines are thermally bonded to provide maximum thermal dissipation to the fixture's exterior to ensure long life. To protect the light engine panel from moisture and corrosion, the LED light engine panel is uniformly coated with a UV-stabilized acrylic polymer resin that meets MIL and ASTM dielectric standards, UL, and IPC standards for flammability, moisture resistance, and thermal shock.

COLOR TEMPERATURE: 2200K, 2700K, 3000K, 4000K, and 5000K.

LED LIFETIME: All LEDs are rated for a minimum of 100,000 hours of continuous operation at ambient temperatures from-40°F/-40°C to 115°F/46°C.

COLOR RENDERING INDEX (CRI): Minimum of 80 or higher. CRI 90+ is available upon request. CRI 90+ is not available in 2200K.

DIMMING: 0-10V standard dimming capability.

SURGE PROTECTION: Thermally protected 20kA/ 40kV varistor type surge suppressor is included and meets ANSI C136.2- 2015: Extreme Level. It also meets IEC61643-11 Class II / EN61643-11 Type 2 and US Dept of Energy MSSLC Model Spec for surge protection. The device is wired in series with the luminaire input power to interrupt power to the luminaire when consumed, protecting the LED power supply and circuit boards from additional electrical surges.

MANUFACTURING ORIGIN: US Manufactured and Assembled.

BABA COMPLIANT: Meets Build America, Buy America Act Included in the Infrastructure Investment and Jobs Act, Public Law Number 117-58, Title IX, Subtitle A, Part I – Buy America Sourcing Requirements, Sections 70911-70917 stating Manufactured in the U.S. The cost of components mined, produced, or manufactured in the U.S. is greater than 55 percent of the total cost of all manufactured product components.

DESIGNLIGHTS CONSORTIUM® (DLC) QUALIFIED PRODUCT: Unless noted, not all versions of this product may be DLC® qualified. For a complete list of Lumecon DLC® Qualified Products visit: www.designlights.org.

CERTIFICATION: Manufactured with ETL-compliant components.

WARRANTY: 10 Year L70 performance-based warranty. For full warranty terms, please visit our website: www.lumecon.com.



Email: sales@lumecon.com Website: www.lumecon.com Phone: 248-477-5009 Copyright © 2023 Lumecon LLC. All Rights Reserved. Note: Specifications and photometric data are subject to change at any time without notice. Please see www.lumecon.com for current specifications and documentation.







PERFORMANCE DATA

		2200K		2700K		3000K		4000K		5000K		
Model	Distribution Type	Watts	Lumens	Efficacy								
	Type 2	45W	4,452	101	4,925	111	5,295	120	5,413	122	5,641	128
LM-BRD-45	Туре 3	45W	4,602	104	5,901	115	5,449	123	5,596	127	5,831	132
	Type 4	45W	4,106	93	5,239	118	5,499	124	5,759	130	6,001	136
	Type 5	45W	4,779	108	5,287	120	5,337	121	5,812	131	6,519	137
LM-BRD-65	Type 2	65W	5,892	94	6,519	104	6,780	108	7,166	114	7,467	119
	Туре 3	65W	6,091	97	6,739	108	7,213	115	7,408	118	7,944	127
	Type 4	65W	6,278	100	6,935	111	7,279	116	7,624	123	8,017	128
	Type 5	65W	6,326	101	6,780	112	7,279	116	7,693	123	8,017	128
LM-BRD-90	Type 2	90W	9,923	109	10,979	121	11,418	126	11,986	133	12,575	139
	Туре 3	90W	10,259	113	11,350	125	12,147	134	12,400	138	13,378	148
	Type 4	90W	10,550	117	11,680	129	12,259	135	12,912	142	13,501	149
	Туре 5	90W	10,605	118	11,813	130	12,224	135	12,877	143	13,500	149

ORDERING INFORMATION

Lumecon Midtown Post-Top Series Example Part Number: LM-BRD-45-1-40-T3-CA-BLK-PC-BL

REQUIRED								OPTIONAL		
MODEL	WATTAGE	VOLTAGE	сст	DISTRIBUTION	LENS	FINISH	PHOTOCELL	HOUSE SIDE SHIELD		
LM-BRD	45 - 45 Watts	1 - 120v - 277v	22 - 2200K	T3 - Type III	CA - Clear Acrylic	See Samples Below	PC - Button Eye	BL - Back Light Louvers		
	65 - 65 Watts	2 - 347v - 480v	27 - 2700K	T5 - Type V	CP - Clear Polycarbonate					
	90 - 90 Watts		30 - 3000K		OA - Opal Acrylic					
			40 - 4000K		OP - Opal Polycarbonate					
			50 - 5000K		PP - Prismatic Polycarbonate					

Available Finishes

Standard						
BLK Black	FGN Forest Green	WHT White	LBR Landscape Brown	BRN Brown	DBZ Dark Bronze	ARB Architectural Bronze SRT Shadow Rust
Premium						
ABS Antique Brass	ACP Antique Copper	VGN Verde	ASI Antique Silver	WBZ Weathered Bronze	RBZ Rustic Bronze	

ARD Antique Red

VCP Verde Copper VTC Vintage Copper

GRA Granite

VBZ Verde Bronze