



COMET HP Cold Water Cleaner



K 200

CLASSIC · EXTRA

Ergonomic handle for easy maneuverability

Maniglia ergonomica per una pratica movimentazione



ON CLASSIC VERSIONS
Without hose reel at the top

SU VERSIONI CLASSIC
Dotazione senza avvolgitubo nella parte superiore

GENERAL FEATURES · CARATTERISTICHE GENERALI

- Sturdy injection-moulded plastic casing
- Handy lance and gun storage
- Handle with supports for the power cable and delivery hose
- Easy maintenance by simply removing the front casing
- Big wheels (220 mm Ø) for easy movement up and down steps and over uneven ground
- Removable detergent tank with level visible from the outside
- Regulated low-pressure detergent suction with filter
- GXR motorpump with brass head and stainless steel pistons (monophase models); AXR motorpump with brass head and ceramic pistons (three-phase models)
- 2-pole motor (2800 rpm)
- Built-in professional unloader valve + pressure gauge
- Total Stop system
- **Self-priming** pumps with EASY START device
- Rotary switch
- Motor thermal protection



MTP GXR · AXR

Motorpump with brass head and stainless steel pistons (GXR) or ceramic pistons (AXR) with valve and pressure gauge

Motopompa con testata in ottone e pistoni in acciaio inox (GXR) o in ceramica (AXR) con valvola e manometro



Removable detergent tank with externally visible level

Serbatoio detergente estraibile con livello visibile esternamente



Can be used vertically or horizontally

Utilizzabile in verticale o in orizzontale



STANDARD EQUIPMENT · DOTAZIONE STANDARD

GC 201 gun with protection Pistola GC 201 con protezione	Bent lance, with adjustable nozzle Lancia angolata, con ugello regolabile	GC 251 gun with protection Pistola GC 251 con protezione	Bent lance with detergent head, with nozzle Lancia angolata con testina detergente, con ugello
EXTRA	CLASSIC	EXTRA	CLASSIC EXTRA
Bent lance, with rotating nozzle Lancia angolata, con ugello rotante	10 m rubber delivery hose kit Kit tubo gomma mandata 10 m	Hose Reel with 15 m rubber delivery hose Avvolgitubo con tubo mandata 15 m	Plastic inlet water filter Filtro ingresso acqua in plastica

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

CODE CODICE	MODELS MODELLI	PUMP POMPA	Ph V Hz			MAX bar MPa		WORK bar MPa		WORK l/h	HP kW	kW	It	kg	(L x W x H) cm	
			Ph	V	Hz	bar	MPa	bar	MPa							
9057 0500	K 200 10/150 M Classic	GXR	1	230	50	150	15	30÷135	3÷13,5	280 ÷ 600	3,0	2,2	2,9	3,5	37	54 x 44 x 68
9057 0501	K 200 10/150 M Extra	GXR	1	230	50	150	15	30÷135	3÷13,5	280 ÷ 600	3,0	2,2	2,9	3,5	47	54 x 44 x 99
9057 0504	K 200 12/130 M Classic	GXR	1	230	50	130	13	30÷115	3÷11,5	360 ÷ 720	3,0	2,2	2,9	3,5	37	54 x 44 x 68
9057 0505	K 200 12/130 M Extra	GXR	1	230	50	130	13	30÷115	3÷11,5	360 ÷ 720	3,0	2,2	2,9	3,5	47	54 x 44 x 99
9057 0506	K 200 12/200 T Classic	AXR	3	400	50	200	20	30÷190	3÷19	290 ÷ 720	5,0	3,7	4,3	3,5	40	54 x 44 x 68
9057 0507	K 200 12/200 T Extra	AXR	3	400	50	200	20	30÷190	3÷19	290 ÷ 720	5,0	3,7	4,3	3,5	50	54 x 44 x 99