



# COMET HP Cold Water Cleaner



MADE IN ITALY

## RC-5

EXTRA

Ergonomic handle for easy maneuverability  
*Maniglia ergonomica per una pratica movimentazione*



**ON CLASSIC VERSIONS**  
Without hose reel at the top

**SU VERSIONI CLASSIC**  
Dotazione senza avvolgitubo nella parte superiore

### GENERAL FEATURES · CARATTERISTICHE GENERALI

- Sturdy injection-moulded plastic casing
- Handy lance and gun storage
- Handle with supports for the power cable and delivery hose
- Easy maintenance by simply removing the front casing
- Big wheels (Ø 210 mm) for easy movement up and down steps and over uneven ground
- Removable detergent tank with level visible from the outside
- Detergent adjustment with filter
- Regulated low-pressure detergent suction
- Pressure gauge
- 4-pole motor (1400 rpm) well oversized and protected with paint
- Built-in professional unloader valve
- Delayed Total Stop
- Self-priming pumps with EASY START device on single-phase models
- Rotary switch
- Motor thermal protection



**LW-K 250**

Pump with 3 integral ceramic pistons. Oil sight glass. Brass pump heads

*Pompa con 3 pistoni in ceramica integrate. Visore livello olio. Testate in ottone*



### STANDARD EQUIPMENT · DOTAZIONE STANDARD

CLASSIC



GC 251 gun with protection  
*Pistola GC 251 con protezione*

EXTRA



GH 281 gun with Swivel and pressure regulator  
*Pistola GH 281 con Swivel e regolatore pressione*

CLASSIC | EXTRA



Bent lance with detergent head  
*Lancia angola con testina detergente*

CLASSIC



10 m rubber delivery hose kit  
*Kit tubo gamma mandata 10 m*

EXTRA



15 m rubber delivery hose kit (on Hose Reel)  
*Kit tubo mandata 15 m (su Avvolgitubo)*

CLASSIC | EXTRA



15° spray nozzle, 1/4" MEG connection  
*Ugello con getto a lama 15°, attacco 1/4" MEG*



Can be used vertically or horizontally

*Utilizzabile in verticale o in orizzontale*



Removable detergent tank with externally visible level

*Serbatoio detergente estraibile con livello visibile esternamente*

EXTRA



Lance with rotating nozzle  
*Lancia con ugello rotante*

CODE CODICE	MODELS MODELLI	PUMP POMPA	Ph V Hz			MAX bar MPa		WORK bar MPa		l/h	HP kW		kW	kg	(L x W x H) cm	€
			Ph	V	Hz	bar	MPa	bar	MPa		HP	kW				
9057 0152	RC-5 MP 10/150 Cl.	LW-K 250	1	230	50	150	15	30±135	3±13,5	280±600	3,0	2,2	2,9	40	54 x 44 x 68	
9057 0154	RC-5 MP 12/130 Cl.	LW-K 250	1	230	50	130	13	30±120	3±12	360±720	3,0	2,2	2,9	40	54 x 44 x 68	
9057 0158	RC-5 TP 13/190 Cl.	LW-K 250	3	400	50	190	19	30±180	3±18	330±780	5,5	4,0	5,0	40	54 x 44 x 68	
9057 0160	RC-5 TP 15/170 Cl.	LW-K 250	3	400	50	170	17	30±160	3±16	300±900	5,5	4,0	5,0	40	54 x 44 x 68	
9057 0151	RC-5 MP 10/150 Ex.	LW-K 250	1	230	50	150	15	30±135	3±13,5	280±600	3,0	2,2	2,9	40	54 x 44 x 68	
9057 0153	RC-5 MP 12/130 Ex.	LW-K 250	1	230	50	130	13	30±120	3±12	360±720	3,0	2,2	2,9	50	54 x 44 x 68	
9057 0157	RC-5 TP 13/190 Ex.	LW-K 250	3	400	50	190	19	30±180	3±18	320±780	5,5	4,0	5,0	50	54 x 44 x 68	
9057 0159	RC-5 TP 15/170 Ex.	LW-K 250	3	400	50	170	17	30±160	3±16	390±900	5,5	4,0	5,0	50	54 x 44 x 68	

• Requires 4 kW single-phase electricity supply · *Richiede rete elettrica monofase da 4 kW*



1400



3,5 lt