

**KÄRCHER**



## HD 13/35 -4 Classic \*CN



4-6 h



AUTO SHUTDOWN

### 1 High-performance crankshaft pump

- Reliable and durable Kärcher high-performance crankshaft pump ensures optimal pressure.

### 3 Reliable and durable

- Longer service life, less maintenance effort and lower costs. Ideal for industrial use.

### 2 Dry run protection

- Protects the pump against dry running.

## TECHNICAL DATA AND EQUIPMENT

**KÄRCHER**

### HD 13/35 -4 Classic \*CN

#### Technical data

Order no.		1.367-158.0
EAN code		4054278242477
Working pressure	bar / MPa	100-350 / 10-35
Flow rate	l/h	500-1300
Max. inlet temperature	°C	max. 60
Drive		E-Motor 400 V / 50 Hz
Motor rating	kW	15
Weight	kg	230
Dimensions (L x W x H)	mm	1110 x 800 x 950

#### Equipment

Electro start		-
High-pressure hose	m	10 / Heavy duty
Spray gun		Industrial trigger gun
Stainless steel lance	mm	700
Flat jet nozzle		■
Water filter		■
Safety valve		■
Elapsed time counter		■

■ Included in the scope of supply.

**HD 13/35 -4 CLASSIC \*CN**  
**1.367-158.0**

**KÄRCHER**



		Order no.	Length			Price	Description	
<b>High-pressure hoses</b>								
Pressure hose	1	6.391-848.0					650 bar, M 22 x 1.5	■
	2	6.391-857.0					650 bar, M 22 x 1.5.	□
<b>Trigger guns</b>								
Kärcher industry gun	3	4.775-824.0					650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	■
<b>Spray lances</b>								
Spray lance	4	4.760-679.0					With nozzle holder.	■
	5	4.760-653.0						□
	6	4.760-675.0						□
	7	4.760-677.0						□
Spray lance extension	8	4.760-699.0					Spray lance extension 800 mm, 65 MPa.	□
<b>Power nozzles</b>								
Flat jet nozzle	9	5.765-166.0					15° flat jet nozzle 15049 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h (electr.).	■
<b>Screw nozzles F21</b>								
Dummy nozzle F21	10	6.025-237.0					F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	□
Round jet nozzle F21, Saphir	11	9.886-216.0					Screw-on F21 sapphire round jet nozzle with a diameter of 0.90 mm. Suitable for working pressures of up to 3,000 bar.	□
<b>Multi-jet rotary nozzles</b>								
Nozzle carrier head TD09	12	9.899-828.0					6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	□

■ Included in the scope of supply. □ Available accessories.