



Fuel Suction & Delivery hose



FSD150 150 PSI Fuel Suction & Delivery Hose

Applications:

Features: Suitable for Heavy duty suction and delivery a tank truck or tank wagon hose it withstands the full vacuum, anti-static cover conforms fully to PTB specifications, a wide range of petroleum products up to 50% aromatics Content.

Tube: Black , smooth, NR/NBR rubber

Reinforcement: High strength synthetic cord with steel helix plus antistatic copper wire

Cover: Black, NBR/CR , Anti-abrasion, weather resistant, synthetic rubber

Working Pressure: 10bar/ B.P 30bar

Temperature range: -40°C to +80°C

Reference Standard: EN1360/EN13483

Branding : Black transfer tape with White text.

"TECHFLEX FSD150 FUEL SUCTION/DELIVERY HOSE WPSI 150"

Specification:

Part No.	I.D.		O.D.		Working Pressure		Burst Pressure		Min. Bend RADIUS	Weight	Length
	Inch	mm	Inch	mm	Bar	Psi	Bar	Psi	mm	Kg/m	Roll/m
FSD150-0200	2"	51	2.55"	65	10	150	30	450	300	2.01	20~60
FSD150-0250	2-1/2"	64	3.14"	80	10	150	30	450	400	3.02	20~60
FSD150-0300	3"	76	3.62"	92	10	150	30	450	400	3.50	20~60
FSD150-0400	4"	102	4.72"	120	10	150	30	450	500	5.10	20~60
FSD150-0500	5"	127	5.78"	147	10	150	30	450	600	7.60	20~60
FSD150-0600	6"	152	6.77"	172	10	150	30	450	600	8.90	20~60

