



Fuel Suction & Delivery hose



FSD300 300 PSI Fuel Suction & Delivery Hose

Applications:

Features: Suitable for Heavy duty suction and delivery a tank truck or tank wagon hose it withstands the full vacuum, anti-static cover conforms fully to PTB specifications, a wide range of petroleum products up to 50% aromatics Content.

Tube: NBR rubber

Reinforcement: High tensile textile cord with helix steel wire & with copper wire

Cover: Black, NBR/CR , Anti-abrasion, weather resistant, synthetic rubber

Working Pressure: 20bar/ B.P 60bar

Temperature range: -40°C to +80°C

Reference Standard: EN1360/EN13483

Branding : Black transfer tape with White text.

"TECHFLEX FSD150 FUEL SUCTION/DELIVERY HOSE WPSI 150"

Specification:

Part No.	I.D.		O.D.		Working Pressure		Burst Pressure		Min. Bend Radas	Weight	Length
	Inch	mm	Inch	mm	Bar	Psi	Bar	Psi	mm	Kg/m	Roll/m
FSD300-0075	3/4"	19	1.21"	30.8	20	300	60	900	200	0.55	20~60
FSD300-0100	1"	25	1.44"	36.8	20	300	60	900	220	0.70	20~60
FSD300-0125	1-1/4"	32	1.83"	46.4	20	300	60	900	250	1.23	20~60
FSD300-0150	1-1/2"	38	2.09"	53	20	300	60	900	280	1.56	20~60
FSD300-0200	2"	51	2.39"	60.8	20	300	60	900	300	2.01	20~60
FSD300-0250	2-1/2"	64	3.2"	81.2	20	300	60	900	400	3.02	20~60
FSD300-0300	3"	76	3.67"	93.2	20	300	60	900	400	3.50	20~60
FSD300-0400	4"	102	4.74"	120.4	20	300	60	900	500	5.10	20~60
FSD300-0600	6"	152	6.88"	174.8	20	300	60	900	600	8.90	20~60

