



## OIL SUCTION/DELIVERY HOSE



### OSD150 150 PSI

### OIL/FUEL SUCTION AND DISCHARGE HOSE

**TEMPERATURE RANGE:** - 35°C to + 100°C

**TUBE:** Oil resistant, conductive synthetic nitrile black rubber.

**REINFORCEMENT:** High tensile synthetic textile, steel wire helix and conductive copper wire

**COVER:** Oil, weather, ozone, abrasion and sea water resistant, special synthetic rubber.

**COILS:** 30/40mt continuous length; other length , size and color available on request.

**BRANDING:** Red transfer tape with White text.

'TECHFLEX OSD150 OIL SUCTION/DELIVERY HOSE WPSI 150'

Part No	I.D.		O.D.		Working Pressure		Bursting Pressure		Weight	Bending Radius
	mm	inches	mm	inches	atm	Psi	atm	Psi		
OSD150-0100	25	1"	35	1-3/8"	10	150	30	450	0.79	150
OSD150-0125	32	1-1/4"	42	1-21/32"	10	150	30	450	0.97	192
OSD150-0150	38	1-1/2"	51	1-31/32"	10	150	30	450	1.40	228
OSD150-0175	45	1-3/4"	57	2-15/64"	10	150	30	450	1.43	266
OSD150-0200	51	2"	62	2-13/32"	10	150	30	450	1.81	306
OSD150-0250	64	2-1/2"	78	3-1/32"	10	150	30	450	2.80	378
OSD150-0300	76	3"	92	3-5/8"	10	150	30	450	2.93	456
OSD150-0350	90	3-1/2"	104	4-3/32"	10	150	30	450	3.46	540
OSD150-0400	102	4"	120	4-47/64"	10	150	30	450	4.95	612
OSD150-0500	127	5"	147	5-51/64"	10	150	30	450	6.60	762
OSD150-0600	152	6"	174	6-25/32"	10	150	30	450	7.80	912
OSD150-0800	203	8"	227	8-15/16"	10	150	30	450	9.00	1650
OSD150-1000	254	10"	282	11-7/64"	10	150	30	450	20.03	2035
OSD150-1200	305	12"	341	13-7/16"	10	150	30	450	28.50	2600