



WATER SUCTION/ DELIVERY HOSE



WSD150 150 PSI

WATER SUCTION/ DELIVERY HOSE

Water Suction & Discharge Hose suitable for a variety of general purposes in industries, construction sites and mines. It handles sewage, waste water, mud & etc.

TEMPERATURE RANGE: -40°C to +85°C

TUBE: Black, smooth, synthetic rubber resistance to water with PH Value 5~8.

REINFORCEMENT: High tensile synthetic cord and a helix wire.

COVER: Black, smooth (wapped finish) synthetic rubber, abrasion & weathering resistant.

APPLICATION: For Pneumatic Equipments and Tools.

COILS: 40mt continuous length; other length, size and color available on request.

BRANDING: Blue transfer tape with White text.

'TECHFLEX WSD150 WATER SUCTION/DELIVERY HOSE WPSI 150'

Part No	Size	I.D.	O.D.	Working Pressure		Bursting Pressure		Weight	Bending Radius
	inches	mm	mm	atm	Psi	atm	Psi		
WSD150-0125	1-1/4	32	43	10	150	30	450	0.97	256
WSD150-0150	1-1/2	38	50	10	150	30	450	1.27	304
WSD150-0200	2	51	63	10	150	30	450	1.72	408
WSD150-0250	2-1/2	63	77	10	150	30	450	2.37	508
WSD150-0300	3	76	89	10	150	30	450	2.79	608
WSD150-0400	4	102	118	10	150	30	450	5.15	816
WSD150-0500	5	127	144	10	150	30	450	7.23	1010
WSD150-0600	6	152	171	10	150	30	450	10.18	1216
WSD150-0800	8	203	224	10	150	30	450	14.80	1624
WSD150-1000	10	254	280	10	150	30	450	16.34	2035
WSD150-1200	12	305	336	10	150	30	450	24.63	2600