




- Hose** : MARINE FUEL HOSE, type FHA115__A
- Application** : Feed / Vent hose for petrol and diesel (yachts and small craft)
- Features** : Small bending radius
- Suitable for the following fluids:
- Diesel fuel
 - Bio Diesel (up to B100)
 - Petrol fuel
 - Oil
 - Ethanol
- Lining** : Translucent nylon for fuel and permeation resistance to 100 °C (212 °F)
- Reinforcement** : Multiple textile plies
- Cover** : Black nitrile/PVC, smooth finish
- Temperature** : Suitable for use in the range -29 to +100 °C (-20 to +212°F)
- Relevant Standards** : ISO 7840, ISO 10088, CE, ABYC, CARB, EPA, SAE J 1527 A1-15, NMMA Type Accepted (2618936 and 2618937), USCG A1
- Vacuum** : Not recommended
- Couplings** : Compliant with ABYC

Code	I.D.		O.D.	Maximum Working Pressure		Minimum Bending Radius		Weight	
	mm	inch	mm	bar	psi	mm	inch	kg/m	lbs/ft
FHA11506A	6	1/4	14	7	100	63.5	2.5	0.16	0.11
FHA11508A	8	5/16	16	7	100	63.5	2.5	0.19	0.13
FHA11510A	10	3/8	17	7	100	63.5	2.5	0.23	0.16
FHA11513A	13	1/2	21	7	100	114.3	4.5	0.29	0.20

Identification:

   <p style="font-size: small; margin: 0;">MARINE FUEL HOSE - I.D. 10 mm ISO7840 - A1 SAE J 1527 USCG TYPE A CLASS 1 - I.D. 3/8 "</p>
<p>Black ribbon with white text over full length of hose 0.3 meter Mark, Hose type and dimension repeated every 0.3 meter</p>