

	PCW3000
Series	Pro
Designed in	2012
Motor/Engine	POWERED by HONDA Honda GX35 4-stroke - 360° inclinable - air-cooled 1.0 kW - 1.3 HP @ 7,000 tr/min
Powered by	Gas
Drive/Clutch	Direct drive (no clutch)
Rope Retention System	No
Drum turns when motor/engine is idling	Yes
Pulling Capacity	
Standard drum (single line / double line)	Ø 3'' (76 mm) : 1,600 lb / 3,200 lb
Optional drum (single line / double line)	No optional drum
Lifting Capacity	
Standard drum (single line / double line)	Not designed for lifting - See INDUSTRIAL States winches
Optional drum (single line / double line)	No optional drum
Speed	
Standard drum	Ø 3'' (76 mm) : 33'/min
Optional drum	No optional drum
Weight	20 lb
Dimensions (overall)	13-3/4" x 11-3/8" x 10-1/4"
Gearbox	Aluminium alloy. Heat treated 3-stage helical & spur gears. Mounted on ball bearings. Oil bath lubrication.
Gear ratio	200:1
Brake	Anti-reversing roller clutch bearing
Rope (not included) Length	Low stretch double braided polyester Unlimited
Minimum diameter	Ø 3/8'' (10 mm)
Maximum diameter	Ø 1/2" (13 mm)
Recommended diameter	Ø 3/8" (10 mm)
Included	Round polyester sling - 2-1/2" x 8'
Warranty	Get 1 additional year of warranty if you register your product at www.portablewinch.com
Private use	5 years
Commercial use Motor/Engine	1 year Honda International Warranty
Certification	CE