



## **PRO** SERIES

## **Gas-Powered**

## **Pulling Winch GX50**



SINGLE LINE PULLING FORCE 2,200 LB



DOUBLE LINE PULLING FORCE **4,400 LB** 



WINCH TILT



360°



SPEED

MAX 44'/MIN



WEIGHT

26.5 LB



**POWER** 

1.47 KW | 2.0 HP



MOTORIZATION

**HONDA 4-STOKE GX50** 



POWERED BY



**GAS** 



ROPE GRABBING SYSTEM ARM



CLUTCH

**CENTRIFUGAL** 



PRIVATE USE WARRANTY **5 YEARS** 









	PCW4000
Series	Pro
Designed in	2020
Motor/Engine	POWERED by HONDA Honda GX50 4-stroke - 360° inclinable - air-cooled 1.47 kW - 2.0 HP @ 7,000 tr/min
Powered by	Gas
Drive/Clutch	Centrifugal
Rope Retention System	Quick release automatic anti roll-back mechanism (ARM)
Drum turns when motor/engine is idling	No
Pulling Capacity	
Standard drum (single line / double line)	Ø 3" (76 mm): 2,200 lb / 4,400 lb
Optional drum (single line / double line)	No optional drum
Lifting Capacity	'
Standard drum (single line / double line)	Not designed for lifting - See INDUSTRIAL STALES winches
Optional drum (single line / double line)	No optional drum
Speed	·
Standard drum	Ø 3" (76 mm): 44'/min
Optional drum	No optional drum
Weight	26.5 lb
Dimensions (overall)	16-1/2" x 11-3/4" x 11-1/4"
Gearbox	Aluminium alloy. Heat treated 3-stage helical & spur gears.  Mounted on ball bearings. Oil bath lubrication.
Gear ratio	200:1
Brake	Anti-reversing roller clutch bearing Low stretch double braided polyester
Rope (not included) Length	Unlimited
Minimum diameter	Ø 3/8" (10 mm)
Maximum diameter	Ø 1/2" (13 mm)
Recommended diameter	Ø 3/8" (10 mm)
Included	Round polyester sling - 2-1/2" x 8'
Warranty	Get 1 additional year of warranty if you register your product at www.portablewinch.com
Private use	5 years
Commercial use Motor/Engine	1 year Honda International Warranty
Certification	CE
	·