

PCW4000-A

Gas-Powered Pulling Winch GX50

PRO SERIES



**SINGLE LINE
PULLING FORCE**
2,200 LB / 1,000 KG



SPEED
MAX 44 FT/MIN / 13.4 M/MIN



WEIGHT
26.5 LB / 12 KG



CLUTCH
CENTRIFUGAL



**ROPE GRABBING
SYSTEM**
ARM

+ INCLUDED with each winch

- 1 • Rope bag
- 2 • 50 m (164 ft) rope
- 3 • RopeWizer™ - The Easy Splice
- 4 • Single pulley
- 5 • Steel locking carabiners 2x
- 6 • Safety Hook with Latch
- 7 • 2 m (6 ½ ft) Polyester sling
- 8 • 2.5 m (8 ¼ ft) round polyester sling



	PCW4000
Series	Pro
Designed in	2020
Motor/Engine	POWERED by HONDA. Honda GX50 4-stroke - 360° inclinable - air-cooled 1.47 kW - 2.0 HP @ 7,000 tr/min
Powered by	Gas
Drive/Clutch	Centrifugal
Rope Retention System	Quick release automatic anti roll-back mechanism (ARM)
Drum turns when motor/engine is idling	No
Pulling Capacity	
Standard drum (single line / double line)	Ø 3" (76 mm) : 2,200 lb / 4,400 lb - 1,000 kg / 2,000 kg
Optional drum (single line / double line)	No optional drum
Lifting Capacity	
Standard drum (single line / double line)	Not designed for lifting - See INDUSTRIAL SERIES winches
Optional drum (single line / double line)	No optional drum
Speed	
Standard drum	Ø 3" (76 mm) : 44'/min - 13.4 m/min
Optional drum	No optional drum
Weight	26.5 lb - 12 kg
Dimensions (overall)	16-1/2" x 11-3/4" x 11-1/4" - 42 cm x 30 cm x 28.5 cm
Gearbox	Aluminium alloy. Heat treated 3-stage helical & spur gears. Mounted on ball bearings. Oil bath lubrication.
Gear ratio	200:1
Brake	Anti-reversing roller clutch bearing
Rope	Low stretch double braided polyester
Length	Unlimited
Minimum diameter	Ø 3/8" (10 mm)
Maximum diameter	Ø 1/2" (13 mm)
Recommended diameter	Ø 3/8" (10 mm)
Warranty	Get 1 additional year of warranty if you register your product at www.portablewinch.com
Private use	5 years
Commercial use	1 year
Motor/Engine	Honda International Warranty
Certification	CE