)1111001 01110000 01100101 01110010 01110100 01100101 01100011 01101000

# **TPMS BOOSTER Boosts The Signals From Our TPMS Sensors To The Hypertech Wireless TPMS Monitor Display** STEP BY STEP INSTALLATION & USERS GUIDE



# **Step 1: Mounting TPMS Booster**



Find a good place to mount the TPMS Booster near the front of your trailer.

### **BOAT TRAILER**

We recommend mounting the TPMS Booster to the winch post high enough to keep the TPMS Booster out of the water but out of the way of the winch operation.

# UTILITY/CAR/EQUIPMENT TRAILER

We recommend mounting the TPMS Booster to a lateral cross bar near the front of the trailer.

# **ENCLOSED/CAMPER TRAILER**

We recommend mounting the TPMS Booster to a lateral cross bar near the front of the trailer as low as possible. The minimizes the obstructions between the wheels and the booster.

# **Step 2: Securing TPMS Booster**



Using the provided double-sided tape AND cable ties, secure the TPMS Booster to your trailer.

### MOUNTING ORIENTATION

Mount the TPMS Booster with the large side of the box parallel to the bumper of your tow vehicle. This aligns the internal antenna for maximum strength and best operation.

# **IMPORTANT NOTE**

Mount the TPMS Booster with the connector pointing down. This will ensure any water would run off the connector.

# **Step 3: Finding Power & Ground (4 or 5-PIN Connectors)**

Typically, your trailer will have one of the two (2) connectors shown on this page or the next. You can use these diagrams to identify the needed power and ground wires.




## **4 PIN OR 5-PIN CONNECTORS**

You will use the power for the tail lights to supply power to the TPMS Booster. This will be a **BROWN** wire. You should be able to connect to this wire near the connector that plugs into the vehicle. You could also connect at a tail light or running light.

### **IMPORTANT NOTE**

You will need to turn on your headlights to power up the TPMS Booster.

# **Step 3: Finding Power & Ground (6-PIN Connector)**





### 6-PIN CONNECTORS

These connectors have two (2) possible wires to supply power to the TPMS Booster. The **BLACK** wire is a constant 12V source. The **GREEN** wire supplies power when the running lights are on. Either can be used.

If you cannot easily access the wiring near the connector, we recommend connecting at a tail light or running light instead.

### **IMPORTANT NOTES**

If you choose to use the "Tail & Running Lights" wire (green) for power, you will need to turn on your headlights to power up the TPMS Booster.

If you choose the constant 12V source (black), the TPMS Booster's "automatic sleep mode" will prevent the unit from draining your vehicle's battery if the vehicle/trailer is parked for extended periods of time.

# **Step 4: Routing Harness**



Route the harness to the power and ground source you identified and cut to length. Secure the harness with the provided zip ties.

# **IMPORTANT NOTE**

Be sure to avoid any pinch points or areas that could damage or chafe the harness over time.

# **Step 5: Connecting Posi-Tap To Trailer Wires**




Connect the large end of the provided Posi-Tap connectors to the power and ground wires you have identified. Do this by unscrewing the large end of the Posi-Tap and then sliding it over the wire. Slide the tapping connector up onto the guide and tighten it down to pierce the wire.

### 4-PIN or 5-PIN CONNECTORS

Some 4-PIN or 5-PIN connectors may have multiple wires for power and/or ground. These are typically all the same color, so refer to the guide above for color coding to properly identify the correct wires. Use a multimeter or test light if necessary.



INSERT HOT WIRE



**TIGHTEN** 

# **Step 6: Connecting Posi-Tap To Harness**



Unscrew the small end of the Posi-Tap connectors you installed in the previous step(s). Slide this over the wire as shown. Be sure to strip the lead wires for the next step.

### **IMPORTANT NOTE**

You will need to strip approximately 3/8"-1/2" of the lead wire for the next step.



### 00 01100101 01110010 01110100 01100101 01100011 01101000


# **Step 7: Connecting Wires To Posi-Tap**



Slide the exposed end of each wire into the binding post area of the appropriate Posi-Tap.

### **IMPORTANT NOTE**

12V = **RED** wire of TPMS Booster Harness Ground = **BLACK** wire of TPMS Booster Harness



SLIDE EXPOSED WIRE INTO BINDING POST


# **Step 8: Tightening Posi-Tap**



Tighten the small end of the Posi-Tap connector snugly which presses and holds the exposed wire end to the binding post creating a secure electrical connection.

### **IMPORTANT NOTE**

The TPMS Booster will immediately start operating when power and ground are connected.



# **Automatic Power Saver Mode**

The Hypertech TPMS Booster has a built-in power saver mode that will activate when the vehicle is not moving for longer than five (5) minutes. This eliminates the need to disconnect the TPMS Booster when the trailer is not in use.

The TPMS Booster will automatically switch back to normal operation when the vehicle begins to move.

# **Product Warranty**

This Hypertech product is warrantied against defects in materials or workmanship for ninety (90) days from the date of purchase. Hypertech's liability under this warranty shall be limited to the prompt replacement of the TPMS Booster if deemed as a defective unit. This limited ninety (90) day warranty is to the original purchaser providing all the information requested is furnished. You must retain a copy of your original sales invoice or receipt. Without proper documentation, a service fee will be applied. Third party resellers and resold units are NOT covered under this warranty. Shipping cost is the sole responsibility of shipper.

Hypertech Tech Department
Phone: 901.382.8888 Fax: 901.373.5290
techsupport@hypertech.com
Office Hours: Monday-Friday, 8am-5pm Central Time





Hypertech • 7375 Adrianne Place • Bartlett, Tennessee 38133

Part #LIT123 © 2022 Hypertech