

## DIY0077 - DIY Simply Mixed Rhutilated



Components List
(1) MRQ8RLLH-FDC-8 - Mixed Rhutilated Quartz Diamond Cut 8 Inch
(1) Z011878 - Gold-plated adjustable snake chain bracelet sliding clasp
(1) FTBW0002 - Soft Flex MEDIUM Gauge 0.019 Inch Diameter Beading Wire
(2) A004833 - 2mm Gold Plated Crimp Tubes

## **Tool Suggestions:**

- Cutter
- Flat Nose Pliers

## Directions:

- 1. Cut a 6 in piece of beading wire (FTBW0002).
- 2. Slide one end of wire (FTBW0002) through crimp bead (A004833), then through one loop end of Z011878, and then back through the same crimp bead (A004833).
- 3. Compress crimp bead using a flat nose beading pliers.
- 4. Slide Mixed Rhutilated Gemstones on beading wire in desired arrangement. Ensure both ends of wire run into the gemstones hiding the "loose" end.
- 5. Add crimp bead (A004833) to the other end of bracelet, then through one loop end of Z011878, and again through the same crimp bead (A004833) and two mixed rhutilated end beads.
- 6. Ensure the beads are firmly together, compress crimp bead using a flat nose beading pliers.