



DIY0122 - DIY Sunset On The Horizon Adjustable Necklace – Gold and Purple Flower Opal Chips

Components List

- (1) PFO6x10CHP - Purple Flower Opal 6x10mm Chips - 15-16 Inch
- (1) Z016456 - 40mm Gold Art Deco Horizon Sunset Charm/Pendant
- (1) Z011946 - Gold Plated Adjustable Wheat Chain Necklace Sliding Clasp
- (1) A022205 - 2x4.2mm Heishi Gold Color Over Brass Spacer Beads
- (1) Z011514 - 5mm Gold Plated 18 Gauge Round Jump Rings - 25 Pack
- (1) A004833 - 2mm Gold Plated Crimp Tubes
- (1) Z001212 - Soft Flex FINE Gauge Satin Silver 0.014 Inch Diameter Beading Wire - 10

Tool Suggestions:

- Chain Nose Pliers
- Flush Cutter
- Flat Nose Pliers

Directions:

1. Attached a 5mm jump ring to the large metal charm. Set this aside for now.
2. Cut a piece of Soft Flex approximately 1-2 feet. That will be more than enough but sometimes it's nice to have more than not enough.
3. Choose the gemstone chips you want to use. This project calls for 18 chips but remember you can add more if you want a longer necklace. You will have plenty of gemstones and metal beads to use.
4. Slide a crimp tube onto one end of the beading wire, slide the same end of the beading wire through one of the jump rings on the adjustable necklace, and then back through the crimp tube. Leave about a ¼" to a ½" tail. *Note – make sure the jump ring is securely closed.
5. Slide the crimp tube close to the jump ring, then using flat nose pliers (or chain nose will work too), do a flat crimp. Make sure the 2 strands of beading wire are not overlapping inside the tube. This will make sure you have a nice, clean, flat crimp.



6. Slide the following onto the beading wire, tucking the tail into the beads as you go:
 - a) 1 metal spacer bead
 - b) 1 gemstone chip
 - c) 2 metal beads
 - d) Repeat c) and d) seven more times
 - e) 1 more gemstone chip
 - f) 1 metal spacer
 - *at this point you should have 9 gemstone chips
 - g) Slide the large pendant on from step one
 - h) 1 metal spacer bead
 - i) 1 gemstone chip
 - j) 2 metal beads
 - k) Repeat j) and k) seven more times
 - l) 1 more gemstone chip
 - m) 1 metal spacer
 - n) Crimp tube

7. Slide this end of the beading wire through the other jump ring on the adjustable necklace, then back through the crimp tube and through a couple of the gemstones and metal beads. Again, make sure the jump ring is securely closed. Your tail will stick out through some of the beads.
8. Situate the beads and make sure there are no gaps.
9. Gently tug the beading wire tail until you have the crimp tube close to the jump ring on the adjustable necklace. Don't tug too tight!
10. Using flat nose pliers (or chain nose will work too), Do another flat crimp. Make sure the 2 strands of beading wire are not overlapping inside the tube. This will make sure you have a nice, clean, flat crimp. Make sure to bring all your beads together against so there are no gaps. Trim the tail of the wire with flush cutter. Tuck any remainder of the tail in between the beads.