



DIY0141 - DIY Enamel Tube Bead Color Block Triple Strand Bracelet

Tool Needed:

-Two Chain Nose or Flat Nose Pliers
-Scissors or Cutter

Components List

- (2)Z018429 - 3mm Silver Enamel Tube Bead - 10 Beads
- (2) Z018432 - 6mm Silver Enamel Tube Bead - 10 Beads
- (1) Z018435 - 3mm Black Enamel Tube Bead - 10 Beads
- (1) Z018437 - 6mm Black Enamel Tube Bead - 10 Beads
- (1) Z018440 - 3mm White Enamel Tube Bead - 10 Beads
- (1) Z018441 - 6mm White Enamel Tube Bead - 10 Beads
- (1) Z018447 - 3mm Turquoise Enamel Tube Bead - 10 Beads
- (1) Z018449 - 6mm Turquoise Enamel Tube Bead - 10 Beads
- (1) Z012176 - Silver Plated Adjustable Wheat Chain Bracelet Sliding Clasp
- (1) A004830 - 2mm Silver Plated Crimp Tubes
- (1) Z001212 - Soft Flex FINE Gauge Satin Silver 0.014 Inch Diameter Beading Wire
- (1) X003062 - 5.5mm Silver Plated 18 Gauge Round Jump Rings - 25 Pack
- (1) Z010356 - 12mm Silver Plated Round Solid Quick Links Rings from Beadalon

Directions:

1. Cut 3 pieces of Soft Flex approximately 7". I tend to cut bigger pieces than needed so cut them at whatever length you like. And sometimes it's nice to have more than not enough.
2. Slide a crimp tube onto one end of the beading wire, slide the same end of the beading wire through one of the Quick Links (Z010356) and back through the crimp tube. Leave about a ¼" to a ½" tail.
3. Slide the crimp tube close to the Quick Links ring, then using flat nose pliers (or chain nose will work too), do a flat crimp. Make sure the 2 strands of beading wire are not overlapping inside the tube. This will make sure you have a nice, clean, flat crimp.



4. Start sliding your beads on in the design of your choice, be sure to tuck the tail into the beads as you go.
5. Slide a crimp tube onto the wire once you have finished adding your beads.
6. Loop this end around another Quick Links ring, and then back through the crimp tube and through a couple of the enamel tube beads. Your tail will stick out through some of the beads.
7. Situate the beads and make sure there are no gaps.
8. Gently tug the beading wire tail until you have the crimp tube close to the Quick Links ring. Don't tug too tight!

9. Using flat nose pliers (or chain nose will work too), do another flat crimp. Make sure the 2 strands of beading wire are not overlapping inside the tube. This will make sure you have a nice, clean, flat crimp. Make sure to bring all your beads together against so there are no gaps. Trim the tail of the wire with flush cutter. Tuck any remainder of the tail in between the beads.
10. TIP - If you find that the bracelet clasp (Z012176) is too long after you've completed your design, you can remove the jump rings, cut the chain to your desired length and put the jump rings back on.

