

## ▶ Zerust® Axxanol™ Spray-G

For superior corrosion protection in a sprayable grease, use Zerust Axxanol Spray-G. It protects in extreme conditions, such as during outdoor storage and overseas shipping.

Axxanol Spray-G provides the protection of a grease in the convenience of a sprayable form. It outperforms many other rust preventative coatings, while being easier to apply and remove, saving time and costs associated with corrosion control. The product has an oily grease consistency and provides advanced corrosion protection for parts and equipment for up to 1 year outdoors and 2 years indoors.

Axxanol Spray-G can be used as a light lubricant while it provides exceptional corrosion protection. The product is resistant to water and is compatible with packaging and most rubber and plastic materials. Test on a small area before use.

### Application Example

A large piece of machinery was coated with Axxanol Spray-G before shipment overseas. It was shipped on the deck and in extreme open-air conditions. The item arrived corrosion-free to the end customer.



### ▶ Benefits

Sprayable multimetal rust preventative coating

Protects in extreme outdoor conditions

Safe for paint and plastic

Non-hazardous\* disposal

Removable with an alkaline cleaner

### Application Type

Storage  
Shipping  
During Operation  
May be used with Zerust VCI packaging

\*Non-Hazardous Disposal: Product in unopened original container prior to use is non-hazardous waste in the United States according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).



Product comes in an aerosol can and can be used for large and smaller items.

## Technical Data

<b>Product Information</b>	Solvent-based corrosion inhibitor spray grease.	
<b>Application</b>	Apply via pressurized spray	
	Application temperature	50 to 90°F (10 to 32°C)
	Coverage	1 lb covers 211 ft <sup>2</sup> (20 m <sup>2</sup> )
	Layer Thickness	1 mil (25 µm)
	Removability	Alkaline cleaner
	VOC content	< 45%
	Flash Point	≥ 142° F (61° C)
	Viscosity at 104°F (40°C)	> 1123 mm <sup>2</sup> per second
<b>Properties</b>	Indoors	Up to 2 years
	Outdoor	Up to 1 year
	Salt Spray ASTM B-117	1500 Hrs
	Packaging/Hermetically Sealed	Up to 5 years
	Metal types	Multimetal protection
<b>Storage Guidelines</b>	Temp	50 to 90°F (10 to 32°C)
	Duration	Up to 2 years

## Availability

Zerust® Axxanol™ Spray-G is sold in a ready-to-use Aerosol can and in bulk pails and drums.

Part Number	Qty
350-M-00023AC	12 oz
350-M-00023PL	5 Gal
350-M-00023DR	55 Gal

## Contact a Zerust Corrosion Expert

Consult a Zerust representative to implement an optimum, cost-effective corrosion prevention system across your production facility and supply chain.

## Safety

- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, [www.zerust.com/warranty](http://www.zerust.com/warranty).

©2015 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor-Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, The ZERUST People®, and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

## Contact Us



A product of:  
Northern Technologies  
International Corp  
4201 Woodland Road  
Circle Pines, MN 55014  
USA

Phone. +1 763.225.6600  
Fax. +1 763.225.6645  
[sales@zerust.com](mailto:sales@zerust.com)  
[www.zerust.com](http://www.zerust.com)