

Electric Towing Tractor ***13,000lbs capacity***

FEATURES

- 13,000 lbs lift capacity
- Regenerative braking function
- CURTIS electronic controller
- Emergency reversing device in the handle provides improved operating safety
- Emergency power disconnect switch
- Braking applied with handle upright and horizontal position, increasing the safety of the truck



Electric Towing Tractor ***13,000lbs capacity***

SPECIFICATIONS

| | | | |
|----------------|--|-------|-----------------|
| Identification | Product model | | SLXTB60 |
| | Power supply | | Electric |
| | Operating type | | Pedestrian |
| | Lifting capacity | Kg | 3000kg |
| | Towing capacity | Kg | 6000kg |
| | Draw-bar-pull At the | Kg | 200kg |
| | Weight (without battery) | Kg | 635 |
| Wheel | Tires | | Polyurethane |
| | Tire size drive end | mm | 230x75 |
| | Tire size load end | mm | 150x60 |
| | Balancing wheel size | mm | 100x50 |
| | Wheels number (x=drive wheel) drive end/load | | 1x-2/4 |
| | Tread width drive end | mm | 568 |
| | Tread width load end | mm | 300 |
| Dimensions | Total height | h1 mm | 1410 |
| | Lift height | h3 mm | 376 |
| | Height of handle in drive position (Max/Min) | h6 mm | 1410/1192 |
| | Overall length | L1 mm | 1431 |
| | Overall width | b1 mm | 850 |
| | Minimum ground | m mm | 70 |
| | Turning radius | Wa mm | 1380 |
| Performance | Travel speed | km/h | 4/6 |
| | Lift speed | mm/s | 28/40 |
| | Lowering speed | mm/s | 45/40 |
| | Max gradeability | % | 5/8 |
| | Service brake | | Electromagnetic |
| Electric Motor | Drive motor rating | kW | 2.5 |
| | Lift motor rating | kW | 2.2 |
| | Battery voltage / | V/Ah | 24/280 |
| | Battery weight | Kg | 250 |
| Others | Type of drive control | | MOSFET Control |
| | Noise level at operator's | dB(A) | 70 |