



HÅFSTRÖMS



SPECIFICATION

Model NO. 106205

Camera

Image Sensor 1/2.9" Full HD CMOS Sensor
Resolution 2MP 1080P
Effective Pixels 1920(H)*1080(V)
Compression H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System PAL/NTSC
Electronic Shutter Time Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimum Illumination 0.01Lux
S/N Ratio 60dB
Scanning System Progressive
Video Output Network
Reset Button Optional

Lens

Focus Length 3.6mm
Focus Control Fixed
Lens Type Fixed
Pixels 3MP

Night Vision

Infrared LED 14μ x 18PCS
Infrared Distance 20M
IR Status Auto Control
IR Power On Manual & Timed mode

Network

Ethernet RJ-45 (10/100Base-T)
Protocol TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP,UDP
ONVIF Support ONVIF 2.4(Profile S/T/G)
P2P YES
POE Optional, Support IEEE 802.3af
Video Delay 0.3S (Within the Lan)
Main Stream 1 2048*1536@20fps
Main Stream 2 1920*1080@30fps
Main Stream 3 1280*720@30fps
Sub Stream 1 720*480@30fps
Sub Stream 2 352*288@30fps
IE Brower IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone iPhone, iPad, Android, Android Pad

Camera Features

Day/Night Color/ B&W (IR-CUT)
Image Config Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern Support
Defog Mode Support
BLC Support
Motion Detection Support
Privacy Masking 3 Rectangular Zone
Recording Mode NVR/CMS/Web
Language Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese



HÅFSTRÖMS



Interface

Audio Optional

General

Housing Metal , IP67

Anti-cut Bracket Optional Wall Bracket

IR Cut Filter YES

Operation Temperature -20°C ~ +60°C RH95% Max

Storage Temperature -20°C ~ +60°C RH95% Max

Power Source DC12V±10%, 750mA

Dimension $\phi 93 \times 74(H)$ mm

Weight 400g