



HÅFSTRÖMS



SPECIFICATION

Model	107018
Camera	
Image Sensor	1/2.8" SONY Low Illumination CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.264+/H.265/MJPEG
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	80°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	60°/S
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	5.35mm-96.3mm
Focus Control	18X Optical Zoom
Night Vision	
Infrared LED	∅ 42x6PCS IR LEDS + 2PCS Laser LED
IR Range	120
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Main Stream1	1920*1080@30fps
Main Stream2	1280*720@30fps
Sub Stream1	800*448@30fps
Sub Stream2	704*576@30fps
Sub Stream3	640*360@30fps
Sub Stream4	352*288@30fps
AI Function	
Smart Analytic	3D Human Tracking、 Intrusion Detection、 Alarm Detection
Tracking effective range	5~80M Speed: 3~12KM/h
Interface	
Audio	2-Way Audio
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	-40℃ ~+70℃
Operating Humidity	≤90% Non Condensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	25.5 x 21.5 x 41.0 (cm)
Weight	3.1Kgs