



HÅFSTRÖMS



SPECIFICATION

Model	107110
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H.265
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~180°
Tilt Rotation Speed	25°/S
Tilt Rotation Range	-45°~40°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	5.1mm-51mm
Focus Control	10X Optical Zoom
Night Vision	
Infrared LED	4PCS Array IR LEDS + 2PCS Laser Lamp
IR Range	100m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2560*1920@20fps
Main Stream2	2560*1440@25fps
Main Stream3	2304*1296@25fps
Main Stream4	1920*1080@25fps
Main Stream5	1280*720@25fps
Main Stream6	640*512@25fps
Sub Stream1	800*448@25fps
Sub Stream2	704*576@25fps
Sub Stream3	640*360@25fps
Sub Stream4	352*288@25fps
Interface	
Audio	Optional
POE	Yes
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6x19.6x16(cm)
Weight	3Kgs