



# HÅFSTRÖMS



## SPECIFICATION

<b>Model</b>		<b>109804</b>
<b>Power</b>	Power Adapter Voltage	Input: 110-240V/AC 50-60Hz
	The maximum power	60W
	Mould	+ -4KV
<b>Protection level</b>	Differential mode	+ -1KV
	Network Port	1~4 port :10/100Mbps PoE Ethernet LAN port WAN1/WAN2 port:10/100Mbps Ethernet WAN port
<b>Network Connector</b>	Transmission Distance	Extend switch is default OFF, state(1~4 port): 100m Extend switch is ON, state:(1~4 port): 200m WAN1/2 port: 100m
	Transmission Medium	Cat5/5e/6 standard network cable
	Network Standard	IEEE802.3/10BASE-T Ethernet IEEE802.3u/100BASE-TX Ethernet IEEE802.3x Flow Control, IEEE802.3af
<b>Network Switch</b>	Maximum Frame Size	1536 Bytes
	MAC address list	2K
	Backplane bandwidth	1Gbps
	PoE Standard	IEEE802.3af
<b>Power Over Ethernet LED Status Indicator</b>	PoE Power Supply Type	End-Span(4/5+;7/8-)
	PoE Power Consumption	af,at Adaptive (every port)
	PoE Ethernet	When the PoE power supply is used, 1-4 LEDs When accessing Ethernet, ports 1-4 are
<b>Environmental</b>	Working temperature	0°C~55°C
	Storage temperature	-40°C~70°C
	Working humidity	10%-90% non-condensing
	Storage humidity	5%-95% non-condensing
	Dimension (L x W x H)	220*140*40
<b>Mechanical</b>	Weight	1.1KG
	Material	SECC
	Color	Dark grey
<b>Stability</b>	MTBF	>30000h