



HÅFSTRÖMS



SPECIFICATION

Model		109808
Power	Power Adapter Voltage	Input: 110-240V/AC 50-60Hz 5
	The maximum power	100W
Protection level	Mould	+ -4KV
	Differential mode	+ -1KV
Network Connector	Network Port	1~8 port : 10/100Mbps PoE Ethernet LAN port WAN1/WAN2 port : 10/100/1000Mbps Ethernet WAN port
	Transmission Distance	Extend switch is default OFF, state(1~8 port): 100m Extend switch is ON, state:(1~8 port): 200m WAN1/WAN2 port: 100m
Network Switch	Transmission Medium	Cat5/5e/6 standard network cable
	Network Standard	IEEE802.3/10BASE-T IEEE802.3u/100BASE-TX IEEE802.3x Flow Control, IEEE802.3az
	Maximum Frame Size	1536 Bytes
	MAC address list	2K
	Backplane bandwidth	1Gbps
Power Over Ethernet LED Status Indicator	PoE Standard	IEEE802.3af/at
	PoE Power Supply Type	End-Span(4/5+;7/8-)
	PoE Power Consumption	af,at Adaptive (every port)
	PoE Ethernet	When the PoE is powered, 1-8 LEDs are green When accessing Ethernet, ports 1-8 are
Environmental	Working temperature	0°C~55°C
	Storage temperature	-40°C~70°C
	Working humidity	10%-90% non-condensing
	Storage humidity	5%-95% non-condensing
	Dimension (L x W x H)	220*140*40
Mechanical	Weight	1.4KG
	Material	SECC
	Color	Dark grey
Stability	MTBF	>30000h