

















	Standard	Result
 Size	ASTM F 2055	177.8 x 1219.2 mm
Pack Contents		3.26m ² / 15 Planks
 Thickness	ASTM F 386	3.0 mm
 Bevel Edge		No
Wear Layer	EN 429	0.5 mm
Surface Treatment		PU Coating
Guarantee*	Commercial	15 years
	Domestic	Lifetime
 Classification	EN ISO 10582 Light Industrial	41: Light Industrial Moderate
	EN ISO 10582 Commercial	32: Commercial General
	EN ISO 10582 Domestic	23: Domestic Heavy
 Reaction to Fire	EN13501-1	Bfl-s1
	EN ISO 11925-2	Pass
	EN ISO 9239-1	Pass
Resistance to Chemicals	EN 423	Class 0
	ASTM F 925	Pass
 Staining Resistance	EN 423	Pass
 Slip Resistance**	DIN 51130	R10
 Light Fastness	EN ISO 105-B02	≥ 6
	ASTM F 1515	< 8
 Abrasion Resistance	EN 660-2	Group P
Flexibility	EN 435	Pass
 Dimensional Stability	EN 434	≤ 0.25%
	ASTM F 2199	Pass
 Acoustic Impact Noise Reduction	EN ISO 717-2 / EN ISO 140-8	ΔLw= 6 dB
 Electrical Behaviour Body Voltage	EN 1815	Voltage: 0.5kV
 Indentation - residual	EN 433	≤ 0.1%
	ASTM F 1914	< 8%
 Castor Chair Continuous Use	EN 425	Pass
 Thermal Resistance	ISO 8301	0.11 W/(m.k) Underfloor Heating Compatible Max 27°C
 VOC Emission	ISO 1600	Indoor Use: Pass
Adhesive	F46 Pressure Sensitive	Yes
	F48+ High Temperature	Yes
Squareness	ASTM F 2055	Pass
Recycling		100% Recyclable

*Subject to terms please see our website,

**Slip Resistance can be affected by surface contamination, product maintenance & use,

For more information call
01604 664855 or email
support@bramptonchase.co.uk



DIN51130

Internal use

Certified Body TÜV Rheinland
Slip Resistance - Class R10
Reaction to Fire - Class B_{fl}-s1



CERTIFIED BY
SCS Global Services