








	Standard	Result
 Size	ISO 24342	304.8 x 457.2 mm
Pack Contents		3.34m ² / 24 Tiles
 Thickness	ISO 24346	2.0 mm
 Bevel Edge		No
Wear Layer	ISO 24340	0.3 mm
Surface Treatment		PU Coating
Guarantee*	Commercial	10 years
	Domestic	Lifetime
 Classification	EN ISO 10582 Commercial	31: Commercial Moderate
	EN ISO 10582 Domestic	23: Domestic Heavy
 Reaction to Fire	EN13501-1	Bfl-s1
	EN ISO 11925-2	Pass
	EN ISO 9239-1	Pass
 Staining Resistance	EN 423	Pass
 Slip Resistance**	DIN 51130	R10
	EN 13893	Class DS
 Light/Colour Fastness	EN ISO 105-B02	≥ 6
PU Weight (g/m²)	ISO 23997	8 ≤ n ≤ 12
Flexibility	ISO 24344:A	Pass
 Dimensional Stability	ISO 24342	≤ 0.20%
 Electrical Behaviour Body Voltage	EN 1815	≤ 2.0
 Indentation - residual	ISO 24343-1	≤ 0.10
 Castor Chair Continuous Use	ISO 4918	≥ 25000
 Thermal Resistance	ISO 23999	-1.5 ≤ n ≤ +0.5 Underfloor Heating Compatible Max 27°C
 VOC Emission	EN16516 / ISO 16000	Indoor Air Comfort: Gold
Adhesive	F46 Pressure Sensitive	Yes
	F48+ High Temperature	Yes
Straightness	ISO 24341	≤ 0.25
Acoustic Impact Noise Reduction	EN ISO 717-2 / EN ISO 140-8	ΔLw= 4 dB
Squareness	ISO 24342	≤ 0.25

*Subject to terms, please see our website,

**Slip Resistance can be affected by surface contamination, product maintenance & use,

For more information call
01604 664855 or email
support@bramptonchase.co.uk



EN14041

Internal use

Notified Body 0766

Slip Resistance - Class R10

Reaction to Fire - Class B_{fl}-s1