




STONES ULTRA

Technical Data

	Standard	Result
 Size	ISO 24342	304.8 x 457.2 mm
Pack Contents		2.51m ² / 18 Tiles
 Thickness	ISO 24346	2.5mm
 Bevel Edge		Micro
Wear Layer	ISO 24340	0.55mm
Squareness	ISO 24342	≤ 0.25mm
Straightness	ISO 24342	≤ 0.35mm
 Dimensional Stability	ISO 23999	≤ 0.15%
Curling after 6h at 80°C	ISO 23999	≤ 0.35mm
Flatness at 23°C	ISO 23999	≤ 0.5mm
Guarantee*	Commercial	15 years
	Domestic	Lifetime
 Classification	EN ISO 10582 Light Industrial	41: Light Industrial Moderate
	EN ISO 10582 Commercial	32: Commercial General
	EN ISO 10582 Domestic	23: Domestic Heavy
 Reaction to Fire	EN13501-1	Bfl-s1
Resistance to Chemicals	EN 423	Pass
Peel Resistance	ISO 24345	≥5.0Kg / 50mm
 Slip Resistance**	DIN 51130	R10
Light Fastness	EN ISO 105-B02	≥ 6
 Abrasion Resistance	EN 660-2	Class T
 Thermal Resistance	ISO 8301	0.02m ² K/W Undefloor Heating Compatible Max 27°C
 Electrical Behaviour Body Voltage	EN 1815	Voltage: 0.5kV
 Indentation - residual	ISO 24343-1	≤ 0.10mm
 Castor Chair Continuous Use	ISO 4918	Pass
Emission of formaldehyde	ENV 717-1	CE Certified
 VOC Emission	AgBB/DiBt	≤ 0.5mg/m ³
Adhesive	F46 Pressure Sensitive	Yes
	F48+ High Temperature	Yes
 Acoustic Impact Noise Reduction	EN ISO 717-2 / EN ISO 140-8	ΔLw= 2 dB

*Subject to terms. please see our website,

**Slip Resistance can be affected by surface contamination, product maintenance & use,

For more information call
01604 664855 or email
support@bramptonchase.co.uk



DIN51130

Internal use

Certified Body TÜV Rheinland
Slip Resistance - Class R10
Reaction to Fire - Class Bfl-s1

