
















	Standard	Result
 <b>Size (Large Plank)</b>	ISO 24342	184.1 x 1219.2 mm / Large Plank
<b>Pack Contents</b>		3.37m <sup>2</sup> / 15 Planks / Large Plank
<b>Size (Herringbone)</b>	ISO 24342	114.3 x 609.6 mm / Herringbone
<b>Pack Contents</b>		3.34m <sup>2</sup> / 48 Planks / Herringbone
 <b>Thickness</b>	ISO 24346	2.5mm
 <b>Bevel Edge</b>		Micro
<b>Wear Layer</b>	ISO 24340	0.55mm
<b>Squareness</b>	ISO 24342	≤ 0.25mm
<b>Straightness</b>	ISO 24342	≤ 0.35mm
 <b>Dimensional Stability</b>	ISO 23999	≤ 0.15%
<b>Curling after 6h at 80°C</b>	ISO 23999	≤ 0.35mm
<b>Flatness at 23°C</b>	ISO 23999	≤ 0.5mm
<b>Guarantee*</b>	Commercial	15 years
	Domestic	Lifetime
 <b>Classification</b>	EN ISO 10582 Light Industrial	41: Light Industrial Moderate
	EN ISO 10582 Commercial	32: Commercial General
	EN ISO 10582 Domestic	23: Domestic Heavy
 <b>Reaction to Fire</b>	EN13501-1	Bfl-s1
<b>Resistance to Chemicals</b>	EN 423	Pass
<b>Peel Resistance</b>	ISO 24345	≥5.0Kg / 50mm
 <b>Slip Resistance**</b>	DIN 51130	R10
 <b>Light Fastness</b>	EN ISO 105-B02	≥ 6
 <b>Abrasion Resistance</b>	EN 660-2	Class T
 <b>Thermal Resistance</b>	ISO 8301	0.02m <sup>2</sup> K/W Underfloor Heating Compatible Max 27°C
 <b>Electrical Behaviour Body Voltage</b>	EN 1815	Voltage: 0.5kV
 <b>Indentation - residual</b>	ISO 24343-1	≤ 0.10mm
 <b>Castor Chair Continuous Use</b>	ISO 4918	Pass
<b>Emission of formaldehyde</b>	ENV 717-1	CE Certified
 <b>VOC Emission</b>	AgBB/DiBt	≤ 0.5mg/m <sup>3</sup>
<b>Adhesive</b>	F46 Pressure Sensitive	Yes
	F48+ High Temperature	Yes
 <b>Acoustic Impact Noise Reduction</b>	EN ISO 717-2 / EN ISO 140-8	ΔLw= 2 dB

\*Subject to terms. please see our website,

\*\*Slip Resistance can be affected by surface contamination, product maintenance & use,

For more information call  
01604 664855 or email  
support@bramptonchase.co.uk



DIN51130

Internal use

Certified Body TÜV Rheinland  
Slip Resistance - Class R10  
Reaction to Fire - Class Bfl-s1

