

CORE ITEM



Sekura-N95V

N95 Vented Flat Fold Respirator

INDIVIDUALLY ADJUSTABLE ALUMINUM CONCEALED NOSE CLIP FOR EXCELLENT FIT

SOFTER INNER AND OUTER LAYER FOR COMFORTABLE FIT

ULTRASONIC WELDED HEAD-STRAPS FOR SECURE SEAL

SOFTER EDGES FOR WORKER COMFORT AND FIT



| SPECIFICATIONS | |
|----------------|-----------------------------|
| CLIN | 100, 1000, 1001, 1002 |
| Manufacturer | Makrite Industries Inc. |
| Model Number | Sekura-N95V |
| SKU | VZ-SK-V |
| NIOSH Number | TC-84A-7643 |
| Packaging | 10 masks/box; 12 boxes/case |

| PRICING | | |
|---------|-----------------------|------------|
| CLIN # | Quantity | Unit Price |
| 100 | 1-1,000,000 | \$1.63 |
| 1000 | 1,000,001-5,000,000 | \$1.59 |
| 1001 | 5,000,001-10,000,000 | \$1.58 |
| 1002 | 10,000,001-15,000,000 | \$1.57 |



Features

Makrite® SEKURA Comfort Series is a vertical folded style which is more flexible around the edges and can adapt to the wearer's facial features. Vertical fold masks fold easily when they are not in use and fit well with goggles or helmets so they are convenient for many different types of worker situations. These models have been designed to easily meet NIOSH's stringent approval requirements for breathing resistance and filtration efficiency.



- Exceptional inside filter for lower breathing resistance
- Individually adjustable plastic nose clip allows user to customize the fit for better seal and helps to reduce eyewear fogging
- Ultrasonic welded head-straps for secure seal
- Neck-worn adjustable buckle design for proper fit
- High density urethane foam nosepiece to reduce leakage and provides worker comfort
- Optional exhalation valve reduces heat and moisture build-up inside the mask to enhance worker comfort for longer work hour



Storage & Transportation

The N95 Series Particulate Respirators have a shelf life of 3 years. End of shelf life is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life (use by date). Product should be stored in clean, dry conditions within the temperature range: -5°C to + 50°C with a maximum relative humidity of <75%. When storing or transporting this product use original packaging provided.