

Model: GLOBE WALL NEPAL Codes: 100086108 - L119165211 Group: G-238 Format: 54,8X15X1,2/2,5



RECOMMENDATIONS			
Recommended adhesive	100031189 SUPER-ONE N GRIS		
Recommended adhesive (wet area)	No Procede		
Recommended joint	No admite rejuntado		
Recommended joint (wet area)	No admite rejuntado		

## ADDITIONAL NOTES

The thickness indicated in the parts code corresponds to the nominal size. However, due to the fact that it is an artisan extraction and manufacture, parts may eventually be served with thicknesses close to the nominal size depending on availability.

LABORATORY TESTS				
Bulk density	2675 Kg/m3	UNE EN 1936:2007*		
Flammability	A1f I/A1	UNE-EN 13501-1:2007+A1:2010*		
Flexural strength	22 MPa	UNE-EN 12372:2007*		
Frost resistance	17.9 MPa	UNE-EN 12371:2011*		
Resistance to abrasion (except g.7-8)	18 mm	UNE-EN 14157:2005*		
Resistance to thermal shock	-0.03%/7.9%	UNE -EN 16140:2011*		
Water absorption at atmospheric pressure	0.21%	UNE-EN 13755:2002*		

FEATURES			
There are consistent color changes between pieces.	Material from an Asian country.		
Material suitable for use on indoor walls.	Gloss-free		
Material suitable for use on outdoor walls.	Material that stands out for having an asymmetrical surface.		
PACKING			

Base unit	PIECES	
Boxes	0.4932 M2/BOX	
Gross weight	34.4282 KG/M2	
Net weight	33.2603 KG/M2	
Pallets	14.796 M2/PAL	
Sale unit	M2	
Units	0.0822 M2/PIECE	

