

Model: NAZARI IFRANE

Codes: 100213784 - L138001061

Group: G-231

Format: 11,5X11,5X1-1,1

Thickness: 11 mm



RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS
Recommended joint	100236806 COLORSTUK GRIS N
Recommended joint (wet area)	100236806 COLORSTUK GRIS N

DIMENSIONAL FEATURES

Length and width deviation	($\pm 0.5\%$ x $\pm 0.5\%$ x $\pm 10\%$) mm	UNE-EN ISO 10545-2*
Orthogonality deviation	± 0.5 MM	UNE-EN ISO 10545-2*
Side straightness deviation	± 0.3 MM	UNE-EN ISO 10545-2*
Surface flatness deviation	($+0.5\%$ / -0.3%) MM	UNE-EN ISO 10545-2*

FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



There are considerable color changes between pieces.

PHYSICAL PROPERTIES

Breaking strength	>600 N	UNE-EN ISO 10545-4*
Coefficient of linear thermal expansion	$< 7 \cdot 10^{-6}$ / (°C)	UNE-EN ISO 10545-8*
Crack resistance	Meets	UNE-EN ISO 10545-11*
Expansion due to moisture	<0.6 mm/m	UNE-EN ISO 10545-10*
Flammability	A1	UNE-EN 13501-1*
Resistance to thermal shock	Meets	UNE-EN ISO 10545-9*
Water absorption	>10% (BIII)	UNE-EN ISO 10545-3*

CHEMICAL PROPERTIES

Resistance to chemicals	GA/GLA/GHA	UNE-EN ISO 10545-13*
Stain resistance	Clase 5	UNE-EN ISO 10545-14*

PACKING

Base unit	PIECES
Boxes	0.3967 M2/BOX
Gross weight	16.4083 KG/M2
Net weight	15.8034 KG/M2
Pallets	33.7237 M2/PAL
Sale unit	M2
Units	0.0132 M2/PIECE

