


Model: INDIC 45X120(A)

Codes: 100244485 - V30800681

Water absorption: BIII - Revestimiento (10%≤E≤20%)

Thickness: 10 mm



DIMENSIONAL FEATURES
UNE-EN ISO 10545-2

Length	1200 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
Thickness	10 MM	+/-5%*
Width	450 MM	

*ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

Breaking strength	1514 N	>600N*
Crazing resistance	Resists 3 cycles	
Modulus of rupture	25.3 N/MM2	>=12N/mm2*

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES
UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

Technical code-1	Use on walls	
------------------	--------------	--

PACKING

Boxes	1.62 M2/BOX	
Pallets	64.7983 M2/PAL	
Units	0.54 M2/PIECE	

System Certification

