

Model: BOTTEGA TOPO PV 120X120(A) Codes: 100288928 - P92051231 Water absorption: BIa - Porcelanico (E<=0.1%) Thickness: 11.5 mm





	DIMENSIONAL FEATURES	
	UNE-EN ISO 10545-2	
Length	1200 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
Thickness	11.5 MM	+/-5%*
Width	1200 MM	
*ISO-13006:2018 UNE-EN 14411:2016		
	MECHANICAL FEATURES	
	UNE-EN ISO 10545-4-6-7-11	
Breaking strength	3740.6 N	>1300N*
Crazing resistance	Resists 3 cycles	
Modulus of rupture	54.4 N/MM2	>=35N/mm2*
*ISO-13006:2018 UNE-EN 14411:2016		
	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995	
Changing by sint and		DAM, Y
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*
*ISO-13006:2018 UNE-EN 14411:2016		
	SCOPE OF USE	
Technical code-1	Use on heavy traffic floors	
	ANTI-SLIP VALUE 901:2017 EX, UNE 41902:2017 EX, DIN-51130 y AST	M C1028
Dynamic coefficient of friction	>0,42	
	>0,42 CL1	
Slip resistance (pendulum-wet) *ISO-13006:2018 UNE-EN 14411:2016		
130-13000.2018 UNE-EN 14411.2010		
	PACKING	
Boxes	1.4401 M2/BOX	
Pallets	54.7235 M2/PAL	
Units	1.4401 M2/PIECE	

System Certification



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.