

Model: TANZANIA SILVER ANT (20MM) 29,5X120(A)

Codes: 100323790

Water absorption: Bla - Porcelanico (E<=0.1%)

Thickness: 20 mm

Family: TANZANIA

Tone variations: V3

Rectified: Yes

Finish: Matte



DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

Thickness	20 MM	+/-5%*
Thickness tolerance	2.5 %	+/-5%*
Width	295 MM	
Length	1200 MM	
Length and width deviation	0.34 %	+/-0.6%*
Squareness deviation	0.34 %	+/-0.5%*
Surface flatness deviation	0.47 %	+/-0.5%*
Side straightness deviation	0.17 %	+/-0.5%*

*ISO-13006:2015 UNE-EN 14411:2017

MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

Breaking strength	≥12000 N	>1300N*
Abrasion resistance	<145 MM3	
Crack resistance	Meets	UNE-EN ISO 10545-11*

*ISO-13006:2015 UNE-EN 14411:2017

HYGIENIC FEATURES

UNE-EN ISO 10545-13-14

Stain resistance	Class 5. Easy cleaning with water	3 Min.*
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*

*ISO-13006:2015 UNE-EN 14411:2017

ANTI-SLIP VALUE

CEN/TS 41901/02, DIN-51130 y ASTM A137.1

Slip resistance (pendulum-wet)	CL3	
Slip resistance (ramp)	R-11	
Slip resistance (bare feet)	C	

*ISO-13006:2015 UNE-EN 14411:2017

SCOPE OF USE

Technical code-1	Use on heavy traffic floors	
------------------	-----------------------------	--

Certified company



Follow the installation and maintenance instructions published and recommended by PORCELANOSA GRUPO, adhering to the legal or regulatory requirements existing on each region.

Do not use cleaning agents containing hydrofluoric acid.

In public spaces, tiles must comply with the anti-slip rating under the DCOF (dynamic coefficient of friction) standards.

For big sizes, it is recommended using flexible modified adhesives applied by back-buttering.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by BUTECH S.A.U.

Being the ceramic material that most resembles natural stone, it can show slight variations in shade, color spots and vein among pieces.

The values of slip resistance and dynamic friction coefficient shown in the catalogue published on the internet, or in commercial documents, generally serve only as guidance and are not binding. Any specific requirements will need to be confirmed when placing the order and always prior to installation.

PACKING

Sales units per box	0.708 M2/BOX	
Sales units per pallet	22.656 M2/PAL	
Sales units per unit	0.354 M2/PIECE	

Certified company



Follow the installation and maintenance instructions published and recommended by PORCELANOSA GRUPO, adhering to the legal or regulatory requirements existing on each region.
Do not use cleaning agents containing hydrofluoric acid.

In public spaces, tiles must comply with the anti-slip rating under the DCOF (dynamic coefficient of friction) standards.
For big sizes, it is recommended using flexible modified adhesives applied by back-buttering.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by BUTECH S.A.U.

Being the ceramic material that most resembles natural stone, it can show slight variations in shade, color spots and vein among pieces.

The values of slip resistance and dynamic friction coefficient shown in the catalogue published on the internet, or in commercial documents, generally serve only as guidance and are not binding. Any specific requirements will need to be confirmed when placing the order and always prior to installation.