

Model: CARRARA BLANCO BRILLO L 44,3X44,3(A)

Codes: 100328050

Water absorption: BIIa - Stoneware (3% < E <= 6 %)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Thickness	8.5 MM	+/-5%*		
Width	443 MM			
Length	443 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		

^{*}ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

PEI 4 / 1500v Abrasion resistance Crazing resistance Resists 3 cycles

HYGIE	ENIC	FEAT	JRES
UNE-EN	SO 10	545-13-1	14:1995

Chemical resistance Class "A" for swimming pools and cleaning products B Min.* (resists attack). Minimum Class "B" for acids and bases Stain resistance Class 5. Easy cleaning with water 3 Min.*

ANTI-SLIP VALUE
EN 16165: 2022 / ASTM C1028

Slip resistance (pendulum-wet) CL0

Sales units per unit

	PACKING	
Sales units per box	1.373734 M2/BOX	
Sales units per pallet	71 /3/179 M2/DAI	

0.196248 M2/PIECE

	SCOPE OF USE	
Technical code-1	4 - Use on medium traffic floors	

System Certification







^{*}ISO-13006:2018 UNE-EN 14411:2016

^{*}ISO-13006:2018 UNE-EN 14411:2016

^{*}ISO-13006:2018 UNE-EN 14411:2016



RECOMMENDED USE LOCATIONS

Single-family dwelling

Indoor Premises - Dry: Room, room, bedroom or other enclosure without direct access to the outdoors.

Collective housing

Indoor Premises - Residential - Dry: Entrance, living room, dining room, professional office with reception of customers

Indoor Premises - Housing - Dry: Bedrooms, personal office, storage room, changing room

Various

Cladding of bonded or mixed facades

Facade cladding with mechanical anchors

Kitchen worktops, bars, restaurants

Public bathroom countertops

System Certification





