



## STUDIO OAK AB 11 MM

Oak AB, a 2-layer construction, is a clean oak with some colour variation and small knots with a matt finish. The product is delivered with both left and right version in the bundles for herringbone installation.

## Herringbone

PRODUCT DETAILS		FACTS		TECHNICAL PRO	TECHNICAL PROPERTIES		
Article Number	111PABEK09KE050	Wood Species	Oak	Moisture	EN13183	7%±2%	
EAN Code	7393969038768	Board	Pattern	content			
Surface treatment	Matt lacquer	Grading	Calm	Minimun Mean Density kg/m³ >500 kg/m³			
Dimensions	490 x 70 x 11 mm	Range	Kährs Master	Reaction To Fire	EN13501-1	Cfl-s1	
Weight per Package x	13.43 kg	Collection	Studio Collection	Formaldehyde Emission	EN717-1	E1	
Area per Package (m²)	2.1	Resandable	2 times				
Area per pallet (m²)	0	Natural/Stained	Natural	Content PCP	CEN/TR14823	3 ≤ 5 x 10-6n	
Package info	Packages may contain start and stop boards.	Brinell Value	3,7	Breaking EN153 Strength N/mm²	EN1533	NPD	
		Joint	Tongue & Groove				
DETAIL DESCRIPTION		Floor heating	Yes	Thermal	EN12664	0,14 W/mK	
Even colour with minor variations. Small sized knots in limited numbers allowed.  COLOUR CHANGE		Warranty	30 years	Conductivity	Conductivity		
		Wear-layer material	Hardwood	Thermal Resistance R-Value .08 (m2K/W)		.08 (m2K/W)	
		Wear-layer thickness	4 mm	Biological Durability	EN350-2	Class 1	
Some muting of colour variation to medium, straw brown.		Thickness	11 mm	CARB2		Compliant	

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.