

Acoustic Tile

To order samples/literature -Email: sales@ceilingscenes.com -Phone: 866-440-6888 -Fax: 248-856-4244



Product Overview

These are low-maintenance, fine-textured, fiberglass acoustical panels that resist sagging. They feature exceptional noise reduction properties (NRC values up to .90), meeting the demands of several commercial applications.

Easy to maintain, their laminated surfaces wipe clean with alcohol or soap and water. Additionally, these panels feature Inherent Performance which means that due to the fiberglass substrate these panels inherently resist the growth of mold and mildew.

Main Benefits

- Exceptional noise reduction with NRC values up to .90 for open-plan offices
- High light-reflective finish (LR-.88) reduces light fixtures and energy use
- Coordinates visually with Mars for open/ closed plan applications
- Compatible with the Logix integrated ceiling system
- Non-directional, monolithic visual reduces installation time and waste
- 30-year lifetime system warranty against visible sag, mold and mildew

Applications

- Open-plan offices

- Waiting Rooms /

Nurses stations-

- Media Rooms

– Restaurants

- Hotel Lobbies

- Libraries

assists in addressing HIPAA standards

- Medical Treatment Rooms

- Offices with indirect lighting
- Substrate – Fiberglass

LEED Credits

Recycled Content: 40% – 42% LEED Recycled Content Contribution: 40% – 41%

MR			EQ			
Waste Reduction	Recycled Content	Regional Materials	Rapidy Renevable Materials	Low-Emitting Materials	Daylight andViews	Acoustical Performance
	•	•			•	•

(UL Classified										
Edge	Panel Size ²	Class	NRC	CAC Min.	LR ³	Recycled Content ¹				
		0	٩		0	۲				
SQ	2'x2'x3/4"	ClassA	.90	20	.88 😡	40%				
	2'x4'x3/4"	ClassA	.90	20	.88 😡	40%				

Configuration Options

Images can be printed on single tiles or enlarged over several tiles. See our web site for layout options. Easily installed in 2'X2' and 2'x4' standard grid systems.

All technical specifications have been provided by the manufacturer to Ceiling Scenes. The addition of printed images on the product may result in changes to the technical specifications provided by the manufacturer to Ceiling Scenes. Ceiling Scenes has not conducted independent testing to determine what, if any, changes to the manufacturer's technical specifications result from the addition of printed images. Ceiling Scenes does not represent or warrant that the addition of printed images on the product will meet specific customer requirements. The products are being provided without warranties of any kind, either express or implied, including, but not limited to merchantability or fitness for a particular purpose.

ASTM E84 surface burning characteristics: (Tested with ink applied)

- Class A
- Flame spread: 25
- Smoke developed: 50

Weight:

-0.38 lb/sq. ft. (3/4" panels)

Maintenance

-Can be cleaned easily with a soft brush