

FEATURES

80% MORE POWER

The Yeti PRO 4000 has a 3600W AC inverter that can handle heavy-duty appliances. It comes with up to 80% more power than previous generation products.

CLASS-LEADING LIFESPAN

Improved LiFePO $_4$ battery tech allows for a longer lifespan. (Up to 10 years of daily use, 4000 + cycles)

HIGH CAPACITY

The Yeti PRO has a 4,000 watt-hour capacity. We also offer the Tank PRO 4000 expansion battery so you scale your system up to 20,000 watt-hours.

FASTER CHARGING

The Yeti PRO 4000 has over 5 times the charging speed of previous generation products and can charge from 0% to 80% in just 2 hours from your wall outlet.

YETI® PRO 4000 SKU: #37500 UPC: 847974009505

BATTERY:

Cell Chemistry: LiFePO₄ (Lithium Iron Phosphate) Pack Capacity: 3994Wh (51.2V 78Ah)

Lifecycles: 4000 (0.5C discharge, climate controlled, 80% original capacity.)

Shelf-life: Charge every 12-18 months (in "main power off" state)

Wall Charge Time: 0-100% in about 3 hours at 1800W **PORTS**:

Input

AC Input: 1800W (120V AC, up to 15A)

 $\label{eq:high-Voltage-DC: 3000W Max (13.3-150V DC, up to 40A)} \\ Low Voltage DC: 275W Max (12.3-28V DC, up to 10A) \\ \\$

Input/Output

Power + Port: Input 3000W AC (90-254V AC, up to 30A), Output 3600W AC (120V AC, up to 30 A)

Expansion Port: To be used with Goal Zero Expansion Modules such as the Tank PRO 4000 (100A, 56V DC Max)

Output

3x USB-A: 18W Max Individually, 54W combined 3x USB-C: 2x at 30W Max, 1x at 100W Max, 160W combined

1x 12V High Power Port: 405W Max (13.5V DC, up to 30A)* 2x 12V 6mm port: 135W Max (13.5V DC, up to 10A)*

What's Included: Yeti PRO 4000 · Yeti/Tank PRO 4000 Cart · AC Charging Cable

1x 12V Car Port: 162W Max (13.5V DC, up to 12A)* 4x AC 20A: 2400W (120V AC) Max per port, 3600W continuous shared**, 7200W Surge 1x AC 30A: 3600W Max (120V AC), 7200W Surge

1x AC 30A: 3600W Max (120V AC), 7200W Surge **GENERAL:**

Expandable: Yes (Up to four Tanks per Yeti Pro 4000) Simultaneous charge and discharge: Yes

Weight (Yeti only): 115.74 lbs (52.5 kg)

Weight (with Cart): 125.73 lbs (57.03 kg) Weight (In Box): 137.79 lbs (62.50 kg)

Dimensions (Yeti only): 21.4 x 13.8 x 14.8 in

(54.36 x 35.05 x 37.59 cm)

Dimensions (Yeti & Roll Cart): 21.4 x 13.8 x 18.1 in (54.36 x 35.05 x 45.9 cm)

Dimensions (In Box): 25.5 x 17.89 x 22 in

(64.77 x 45.47 x 55.88 cm)

Operating Usage Temperature: Charge: 32° to 126°F (0° to 52° C) Discharge: -4° to 140°F (-20° to 60°C)

Certs: ® E RoHS

UL 2743, IEC 62368, UL/IEC 62133, UN 38.3 Limited Warranty: 5 years***





*Max of 30 Amps shared across all 12V output ports.

**Shared across all 5 AC ports, 20A and 30A

NOTE: All DC outputs are regulated.

^{***}For warranty terms, conditions, and registration, go to www.goalzero.com/warranty.