

GREAT LAKES WOOD FLOORS HAS A SUPERIOR SELECTION OF HARDWOOD FLOORING.

Great Lakes Wood Floors is pleased to offer some of the best selling colors, species, and innovative surfaces in the hardwood flooring industry. Our slow, deliberate manufacturing processes, superior milling, and careful visual inspection of every piece results

in a precision built floor for fast and accurate installation. Each board is finished with our tough aluminum oxide topcoat and is carefully selected to provide high quality hardwood flooring that will enhance nearly any living space for years to come.

FLOOR CARE

Caring for your hardwood floor is easier than ever, thanks to today's modern finishes. Simply follow these guidelines to assure maximum performance for years to come.

Spills & Spots - Immediately wipe up any spills or spots with a damp cloth.

Vacuum or Sweep - At least every other week, depending on the foot traffic. Don't let sand and dirt build up.

Protect - In areas of high traffic, use area rugs to keep wear to a minimum. Move the rugs occasionally to maintain an even color to your finish. Make sure that the rugs have a backing with a mesh or grid pattern which allows the floor to breathe and are approved for hardwood floor finishes. Put mats at all entrances to keep dirt and moisture off the floor. Use felt pads, wide vinyl pads or rubber rollers on the legs of furniture.

Moving - When moving heavy furniture or appliances, place a sheet of masonite or plywood under the piece that is being moved to distribute the weight and reduce denting or scratching.

Monthly - Clean with a no wax wood floor cleaner.

Be Aware - Of high heel shoes that have lost their protective cap as well as small stones as they can scratch and gouge your floor's surface. Excessive sunlight should be blocked with blinds or drapes. Wet mopping and excessive water can also be harmful to your floor.

Humidity - Never shut off your heating, ventilation or air-conditioning system for long periods of time, such as summer vacations.

WOOD FLOORING HAS A COMFORT LEVEL, TOO.

Wood Flooring will perform best when the interior environment is controlled to stay within a relative humidity range of 30 to 50 percent and a temperature range 60 to 80 degrees Fahrenheit. Fortunately, that's about the same comfort range most people enjoy. The chart below indicates the moisture content wood will likely have at any given combination of temperature and humidity. Note that equilibrium moisture contents in the recommended temperature/humidity range (shaded area) coincide with the 6 to 9 percent range within which most hardwood flooring is manufactured. Although some movement can be expected even between 6 and 9 percent, wood can expand and shrink dramatically outside that range.

MOISTURE CONTENT OF WOOD AT VARIOUS TEMPERATURES AND RELATIVE HUMIDITY READINGS

Temperature (°Fahrenheit)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	98
30	1.4	2.6	3.7	4.6	5.5	6.3	7.1	7.9	8.7	9.5	10.4	11.3	12.4	13.5	14.9	16.5	18.5	21.0	24.3	26.9
40	1.4	2.6	3.7	4.6	5.5	6.3	7.1	7.9	8.7	9.5	10.4	11.3	12.4	13.5	14.9	16.5	18.5	21.0	24.3	26.9
50	1.4	2.6	3.7	4.6	5.5	6.3	7.1	7.9	8.7	9.5	10.4	11.3	12.4	13.5	14.9	16.5	18.5	21.0	24.3	26.9
60	1.3	2.5	3.6	4.6	5.4	6.2	7.0	7.8	8.6	9.4	10.2	11.1	12.1	13.3	14.6	16.2	18.2	20.7	24.1	26.8
70	1.3	2.5	3.5	4.5	5.4	6.2	6.9	7.7	8.5	9.2	10.1	11.0	12.0	13.1	14.4	16.0	17.9	20.5	23.9	26.6
80	1.3	2.4	3.5	4.4	5.3	6.1	6.8	7.6	8.3	9.1	9.9	10.8	11.7	12.9	14.2	15.7	17.7	20.2	23.6	26.3
90	1.2	2.3	3.4	4.3	5.1	5.9	6.7	7.4	8.1	8.9	9.7	10.5	11.5	12.6	13.9	15.4	17.3	19.8	23.3	26.0
100	1.2	2.3	3.3	4.2	5.0	5.8	6.5	7.2	7.9	8.7	9.5	10.3	11.2	12.3	13.6	15.1	17.0	19.5	22.9	25.6

Chart taken from Wood Handbook; Wood as an Engineering Material, (Agriculture Handbook 72), Forest Products Laboratory, U.S. Department of Agriculture




GREAT LAKES WOOD FLOORS


GREAT LAKES
WOOD FLOORS
Toll Free (855) 300-0572
www.GreatLakesWoodFloors.com

Front Cover: Hickory Natural

Printed in the USA 3/14
 Item No. 16397
 AC 64817 5000

SOLID



- 3/4" Solid
- Nail Down or Staple Down Installation; NO glue down
- Plywood, Wood, or OSB Subfloors ONLY
- 50 Year Finish Warranty *

* Note: Timber Ridge carries a 15 Year Finish Warranty



Red Oak Natural
Widths: 2 1/4", 3"




Oak Caramel
Widths: 2 1/4", 3"




Oak Saddle
Widths: 2 1/4", 3"



Oak Honey
Width: 3"




Oak Whiskey Barrel
Wire Brushed
Width: 4"



Oak Cracked Pepper
Wire Brushed
Width: 4"



Oak Mocha Latte
Wire Brushed
Width: 5"



Oak Tanned Leather
Wire Brushed
Width: 4"




Maple Natural
Widths: 2 1/4", 3"




Maple Misty Morning
Width: 3"



Maple Bordeaux
Widths: 2 1/4", 3"




Maple Cappuccino
Widths: 2 1/4", 3"



Hickory Sundance
Widths: 3", 4"



Hickory Saddle
Widths: 3", 4"



Hickory Natural
Width: 3"



Andiroba Natural
Width: 3 1/4"




Cumaru Natural
Width: 3 1/4"



Brazilian Cherry Natural
Width: 3 1/4"




Tigerwood Natural
Width: 3 1/4"




Oak Ebony
Hand Sculpted
Width: 4"




Oak Saddle
Hand Sculpted
Width: 4"




Maple Dark Rum
Hand Sculpted
Width: 4"




Maple Dark Coffee
Hand Sculpted
Width: 4"



Maple Fall Harvest
Hand Sculpted
Width: 4"



Hickory Saddle
Hand Sculpted
Width: 4"




Walnut Provincial
Hand Sculpted
Width: 4"




TIMBER RIDGE
Oak Cocoa
Width: 2 1/4"
15 YEAR
FINISH WARRANTY

ENGINEERED



- Glue Down, Staple Down or Floating Installation
- Concrete, Plywood, Wood, or OSB Subfloors ONLY
- 25 Year Finish Warranty



1/2" Brazilian Cherry
Natural
Widths: 3", 5"



1/2" Tigerwood Natural
Widths: 3", 5"



1/2" Amendoim Natural
Widths: 3", 5"




1/2" Cumaru Natural
Widths: 3", 5"




3/8" Maple Natural
Widths: 3", 5"




3/8" Hickory Natural
Widths: 3", 5"




3/8" Hickory
Burnt Cinnamon
Widths: 3", 5"




3/8" Hickory Saddle
Widths: 3", 5"



3/8" Walnut English Manor
Hand Sculpted
Width: 5"




3/8" Maple Dark Coffee
Hand Sculpted
Width: 5"



3/8" Maple Macchiato
Hand Sculpted
Width: 5"



3/8" Hickory Champagne
Hand Sculpted
Width: 5"



3/8" Hickory Saddle
Hand Sculpted
Width: 5"