

SECTION: _____

 PART: _____



PRODUCT SUBMITTAL DATA

DuraMark™ C Clear Pipe Marker



DuraMark™ C Clear Pipe Markers is a practical, economical marking system featuring bold gothic characters printed on a clear background allowing the pipe color to serve as background color. DuraMark™ C Pipe Markers are manufactured with the industries most durable, long lasting vinyl with an aggressive acrylic adhesive. Available in 5 sizes to mark color coded pipes from 3/4" to over 10"

DESCRIPTION: DuraMark™ C Clear Pipe Markers are designed to help you meet builders specifications that specify color coded piping systems. Sturdy .004" clear vinyl printed using UV screen inks which hold up to sun & weather.

USE: Letter size complies 100% to ASME (ANSI) A13.1-2020 scheme for the Identification of Piping Systems.

LEED Compliance: This product is in compliance with Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule#1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). Self-Stick adhesive backing contains less than 4.4g/Liter volatile organic compounds.

•DURAMARK™ C Application Guide

*For pipes with outside diameters of .75" to 1.25"
 .50" Characters*

- **Style 1 XSM**



*For pipes with outside diameters of 1.5" to 2"
 3/4" Characters*

- **Style 1 SM.**



*For pipes with outside diameters of 2.25" to 6"
 1.25" Characters*

- **Style 1**



*For pipes with outside diameters of 6" to 10"
 2.5" Characters*

- **Style 1 LG**



*For pipes with outside diameters of over 10"
 3.5" Characters*

- **Style 1 XLG**



•STANDARD COLORS

BLACK TEXT

WHITE TEXT

YELLOW TEXT

BLUE TEXT

GREEN TEXT

PURPLE TEXT

ORANGE TEXT

BROWN TEXT

GRAY TEXT

RED TEXT

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____

DuraMark™ C Clear Pipe Marker (Continued)

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE: VERY GOOD

MOISTURE RESISTANCE: EXCELLENT moisture resistance

ABRASION RESISTANCE: VERY GOOD abrasion resistance

GLOSS: 40 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

WARRANTY: Craftmark Pipe Marker products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability for his intended use in his geographic location. Craftmark Pipe Markers warrants to the buyer that its products are free from defects in material & workmanship, but limits its obligation to replacement of the product only. This warranty is in lieu of any other warranty, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular use, and of any other obligations or liability on Craftmark Pipe Marker's part. Under no circumstance will Craftmark Pipe Markers be liable for any loss, damage, expense or consequential damages of any kind arising in connection with the use, or inability to use Craftmark Pipe Marker products.

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____
