

SECTION: \_\_\_\_\_  
 \_\_\_\_\_  
 PART: \_\_\_\_\_  
 \_\_\_\_\_



# PRODUCT SUBMITTAL DATA

## DuraMark™ DM Self-Stick Duct Markers

**DESCRIPTION:** Sturdy 4 mil vinyl with an aggressive permanent adhesive backing. Marker comes with detachable arrow to indicate flow in either direction. Clearly identifies duct work for easy tracking and maintenance.



DuraMark™ DM Duct Markers will make HVAC Maintenance easy and safer and cost effective by clearly identifying duct work. Markers are available in two popular sizes- both come with detachable arrow to indicate flow in either direction.

**FEATURES;**

- Durable self-stick aggressive vinyl
- Indoor /outdoor grade
- Peel off liner for easy application
- 2 sizes to choose from
  - 2 1/4" x 16" (57mm X 152mm) with 1.25"(32mm) Letters
  - 4" x 28" (101mm X 711mm) with 3"(76mm) Letters
- Markers supplied with detachable arrow
- Custom legends & colors at no additional charge

<b>STOCK LEGEND LIST</b>						
<b>SIZE</b>	<b>2 1/4" X 16" (57mm X 152)</b>			<b>4" X 28" (101mm X 711)</b>		
<b>LEGEND</b>	<b>Black on Yellow</b>	<b>White on Green</b>	<b>White on Blue</b>	<b>Black on Yellow</b>	<b>White on Green</b>	<b>White on Blue</b>
<b>EXHAUST</b>	10881-DM	10882-DM	10883-DM	10774-DM	10775-DM	10766-DM
<b>EXHAUST AIR</b>	10884-DM	10885-DM	10886-DM	10776-DM	10777-DM	10767-DM
<b>INTAKE</b>	10887-DM	10888-DM	10889-DM	10778-DM	10779-DM	10768-DM
<b>OUTSIDE AIR</b>	10890-DM	10891-DM	10892-DM	10780-DM	10769-DM	10769A-DM
<b>RELIEF</b>	10893-DM	10894-DM	10895-DM	10781-DM	10782-DM	10770-DM
<b>RELIEF AIR</b>	10896-DM	10897-DM	10898-DM	10783-DM	10784-DM	10771-DM
<b>RETURN AIR</b>	10899-DM	10900-DM	10901-DM	10785-DM	10772-DM	10786-DM
<b>SUPPLY AIR</b>	10902-DM	10903-DM	10904-DM	10773-DM	10787-DM	10788-DM

**• STANDARD COLORS**



DATE: \_\_\_ / \_\_\_ / \_\_\_      JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

# DuraMark™ DM Self-Stick Duct Markers (Continued)

---

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

---

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

---

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

---

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

---

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

---

CHEMICAL RESISTANCE: VERY GOOD

---

MOISTURE RESISTANCE: EXCELLENT moisture resistance

---

ABRASION RESISTANCE: VERY GOOD abrasion resistance

---

GLOSS: 40 Gardner units (20° test)

---

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

---

DATE: \_\_\_ / \_\_\_ / \_\_\_

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

---