

SECTION: _____

 PART: _____



PRODUCT SUBMITTAL DATA

DuraMark™ Direction Flow Arrow Tape



DESCRIPTION: Indoor/Outdoor grade 4 mil vinyl is excellent for indicating flow direction along with Craftmark Pipe Markers. Full 30 yard rolls.

USE: Direction Flow Arrow Tape can be used by itself to indicate flow direction as well as with DuraMark™ Pipe Markers to comply 100% to ASME (ANSI) A13.1-2020.

COMPLIANCE: ASME (ANSI A13.1-2020 Scheme for the Identification of Piping Systems. ANSI Z535.1 Safety Color Codes.

Widths Available: 1/2", 1", 2", 4", 6"
Custom Colors Available.

CRAFTMARK'S ARROW TAPE is the finishing touch for our DuraMark™ pipe marker system. Combines color coding with arrows for cost & labor savings!

- Ultra-Durable self stick vinyl
- Matching color combinations meet ASME(ANSI) A13.1-2020 standards
- Serves to secure markers to pipe as well as indicate flow direction.
- Provides 360° visibility of flow direction
- 30 yard rolls
- Available in 5 stock widths!
- Available in custom color combinations

•Tape Width Guideline	
TAPE SIZE	USE WITH MARKER SIZE
1/2" x 30 yds	1 XSM
1" x 30 yds	1 SM
2" x 30 yds	1
4" x 30 yds	1LG
6" x 30 yds	1 XLG

COLOR BKND / ARROW	
Safety	Yellow / Black
Safety	Red / White
Safety	Green / White
Safety	Blue / White
Safety	Green / Black
Safety	White / Black
Safety	Brown / White
Safety	Gray / White
Safety	Orange / Black
Safety	Purple / White
Safety	Black / White
Safety	Purple / Black
	Clear / White
	Clear / Black

Pipe Diameter	Number of Bands Per Roll	Pipe Diameter	Number of Bands Per Roll
1"	344	6"	57
2"	172	7"	49
3"	115	8"	43
4"	86	9"	38
5"	68	10"	34

DATE: ___ / ___ / ___ JOB: _____
 CONTRACTOR: _____

DuraMark™ Direction Flow Arrow Tape (Continued)

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE: VERY GOOD

MOISTURE RESISTANCE: EXCELLENT moisture resistance

ABRASION RESISTANCE: VERY GOOD abrasion resistance

GLOSS: 40 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____