

SECTION:

PART:

 **CRAFTMARK**
PIPE MARKERS ▲ SINCE 1959
GLOBAL MECHANICAL IDENTIFICATION SOLUTIONS™



PRODUCT SUBMITTAL DATA

DuraMark™ -R Reflective Self-Stick Pipe Marker



Craftmark's DuraMark™-R is pipe marker system that's the ultimate in safety. Meets ASME(ANSI) A13.1-2020 specifications 100%. Manufactured using durable indoor/outdoor engineer grade reflective vinyls with durable UV screen inks. Now available in 5 stock sizes to mark pipes with outside diameter of .75" to over 10". Craftmark sizes, color schemes and letter height all meet ASME (ANSI) A13.1 -Scheme for the Identification of Piping Systems.

FEATURES

- Indoor / Outdoor Use
- **Meets ASME (ANSI) A13.1-2020 100%**
- Bright ASME conforming background colors!
- Letter height meets ASME specifications.
- Color field width meets ASME specifications
- Matching arrow tape available.
- Durable, premium grade, indoor/outdoor reflective vinyl
- Rugged UV screens inks
- Excellent adhesion to piping and insulation.
- Custom Only

● DuraMark™-R Application Guide

For pipes with outside diameters of .75" to 1.25".
.50" Characters

• Style 1 XSM

.75"

For pipes with outside diameters of 1.5" to 2".
.75" Characters

• Style 1 SM.

1.50"

For pipes with outside diameters of 2.25" to 6".
1.25" Characters

• Style 1

2.25"

For pipes with outside diameters of 6" to 10".
2.5" Characters

• Style 1 LG

4"

For pipes with outside diameters of over 10".
3.5" Characters

• Style 1 XLG

4"

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____

DuraMark™ -R Reflective Self-Stick Pipe Marker (Continued)

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE: VERY GOOD

MOISTURE RESISTANCE: EXCELLENT moisture resistance

ABRASION RESISTANCE: VERY GOOD abrasion resistance

GLOSS: 40 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

WARRANTY: Craftmark Pipe Marker products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability for his intended use in his geographic location. Craftmark Pipe Markers warrants to the buyer that its products are free from defects in material & workmanship, but limits its obligation to replacement of the product only. This warranty is in lieu of any other warranty, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular use, and of any other obligations or liability on Craftmark Pipe Marker's part. Under no circumstance will Craftmark Pipe Markers be liable for any loss, damage, expense or consequential damages of any kind arising in connection with the use, or inability to use Craftmark Pipe Marker products.

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____
