AL	SECTION:
BM	PART:







PRODUCT SUBMITTAL DATA DuraMarkTM Self-Stick Pipe Marker



<u>DESCRIPTION</u>: DuraMark™ is a durable indoor/outdoor pipe marker system. Sturdy .004" vinyl printed using UV screen inks which hold up to sun & weather. <u>USE</u>: Use to identify piping systems per ASME (ANSI) A13.1-2020 when used with either pipe banding tape or direction flow arrow tape. Can be used indoor or outdoor.

<u>COMPLIANCE:</u> Complies 100% to ASME (ANSI) A13.1-2020 Scheme for the Identification of Piping Systems for color, color field width & letter size. Complies with ANSI Z535.1 Safety Color Code & CID-A-A-1689A/B

<u>•LEED Compliance:</u> This product is in compliance with Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule#1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). Self-Stick adhesive backing contains less than 4.4q/Liter volatile organic compounds.

Craftmark's DuraMark™ Pipe Marker is a practical, economical marking system featuring bold gothic characters printed on bright ASME conforming colors to provide unmistakable identification of pipe contents. DuraMark™ Pipe Markers are manufactured with the industries most durable, long lasting vinyl with an aggressive acrylic adhesive. Now available in 5 stock sizes to mark pipes with outside diameter of 3/4" to over 10". Craftmark sizes, color schemes and letter height all meet ASME (ANSI) A13.1-2020 -Scheme for the Identification of Piping Systems.

FEATURES

- · Indoor / Outdoor Use
- Meets ASME (ANSI) A13.1-2020 100%
- · Bright ASME conforming background colors.
- · In-Stock legends for immediate shipment.
- · Letter height meets ASME specifications.
- Color field width meets ASME specifications
- · Matching arrow tape available.
- · Durable, premium grade, indoor/outdoor vinyl
- Rugged UV screens inks
- · Excellent adhesion to piping and insulation.
- Use with arrow tape or individual arrows to indicate flow direction.
- · Choose from over 385 stock legends.
- Custom markers available with no minimums.

DuraMark[™] Application Guide

For pipes with outside diameters of 3/4" to 11/4".

1/2" Characters

• Style 1 XSM

1/2" 140° HOT WATER 3/4"

For pipes with outside diameters of 1½" to 2". 3/4" Characters

• Style 1 SM.

3/4" COMPRESSED AIR 11/2"

For pipes with outside diameters of 21/4" to 6". 1 1/4" Characters

• Style 1

11/4" FIRE PROTECTION WATER 21/4"

es with outside diameters of 6" to 10"

For pipes with outside diameters of 6" to 10". 2 1/2" Characters

• Style 1 LG



For pipes with outside diameters of over 10". 3 1/2" Characters

Style 1 XLG

NATURAL GAS 4

STANDARD COLORS

FLAMMABLE FLUIDS

SAFETY YELLOW

POTABLE, COOLING, BOILER FEED & OTHER SAFETY GREEN

COMPRESSED AIR

SAFETY BLUE

FIRE QUENCHING FLUIDS
SAFETY RED

TOXIC & CORROSIVE FLUIDS

SAFETY ORANGE

COMBUSTIBLE FLUIDS
SAFETY BROWN

USER DEFINED

SAFETY PURPLE

USER DEFINED

SAFETY WHITE

USER DEFINED

SAFETY GRAY

USER DEFINED

SAFETY BLACK

DATE: <u>//</u>	JOB:	 	
CONTRACTOR:			

DuraMark™ Self-Stick Pipe Marker (Continued)

	manent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe vering materials.
	ge.e.
SURFACE PREP	ARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.
SERVICE TEMPE	ERATURE: -40°F to 200°F (-40°C to 93°C)
APPLICATION TE	EMPERATURE: Minimum application temperature of 50°F (10°C)
AVERAGE OUTD	OOR DURABILITY: 5 years outdoor - mid continental U.S.
CHEMICAL RESI	ISTANCE: VERY GOOD
MOISTURE RESI	ISTANCE: EXCELLENT moisture resistance
ABRASION RESI	STANCE: VERY GOOD abrasion resistance
GLOSS: 40 Gard	dner units (20° test)
STORAGE STAB	ILITY: 2 years typical at 70°F (21°C) at 50% relative humidity
dete war repl not or li loss	ftmark Pipe Marker products are sold with the understanding that the buyer will test them in actual use and ermine for himself their adaptability for his intended use in his geographic location. Craftmark Pipe Markers rants to the buyer that its products are free from defects in material & workmanship, but limits its obligation to accement of the product only. This warranty is in lieu of any other warranty, expressed or implied, including, but limited to any implied warranty of merchantability or fitness for a particular use, and of any other obligations ability on Craftmark Pipe Marker's part. Under no circumstance will Craftmark Pipe Markers be liable for any s, damage, expense or consequential damages of any kind arising in connection with the use, or inability to use ftmark Pipe Marker products.
E: / /	JOB:
	50D
ITRACTOR:	