

SECTION: \_\_\_\_\_  
 \_\_\_\_\_  
 PART: \_\_\_\_\_  
 \_\_\_\_\_



## PRODUCT SUBMITTAL DATA

### Engraved Phenolic Plastic Nameplates



**DESCRIPTION:** Tough thermoset nameplate with contrasting color layers. Excellent for all types of marking in industrial environments. Non-flammable, scratch resistant plastic that is also resistant to chemical and solvents, Limited color availability.

**USE:** Indoor use only.

Craftmark's Phenolic nameplates and signs are made from a non-conductive plastic which meets Mil-Std-387A Type N.D.P., LP-509, ASTM D 709, ES-1, ES-2, ES-3, LP-387. Extremely durable, heat resistant, non flammable and chemical and solvent resistant. Indoor use only. Non-bending material is great for any flat application. Choose from 3Ply 1/16" or 3Ply 1/8" thick materials. Available with holes or adhesive backing.

#### STANDARD COLORS AVAILABLE



DATE: \_\_\_ / \_\_\_ / \_\_\_

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

# Engraved Phenolic Plastic Nameplates (Continued)

---

ADHESIVE: Available with holes or with 2 mil 3M 467MP adhesive backing.

---

SURFACE PREPARATION: None needed for screw attachment. For adhesive attachment the surface must be clean, dry & oil free.

---

SERVICE TEMPERATURE: -30°F to 200°F

---

APPLICATION TEMPERATURE: N/A for screw attached.  
50°F for adhesive attachment.

---

AVERAGE OUTDOOR DURABILITY: Not recommended for extended outdoor use.

---

CHEMICAL RESISTANCE: EXCELLENT

---

MOISTURE RESISTANCE: GOOD

---

ABRASION RESISTANCE: EXCELLENT

---

GLOSS: 85 Gardner units

---

STORAGE STABILITY: Indefinite for screw attached.  
2 years for adhesive attached at 70°F at 50% relative humidity.

---

DATE: \_\_\_ / \_\_\_ / \_\_\_

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_